

VM-19PD

SKU: 212466



19" (48cm) LCDI Monitor, 1280x1024, 1x Composite, HDMI, RGB, Audio, 12V

Main Features

Professional LCD monitor	1xCVBS,HDMI,RGB and audio input
Built to run 24/7/365 continuously	Quick signal switching (0,8sec.)
PAL/NTSC auto selection	Integrated loudspeakers
Multi-lingual on-screen menu driven setup	Supply voltage: 12VDC
3D-comb filter, Anti Burn- in technology	Robust and compact plastic cabinet
Resolution of 1280x1024 px. (SXGA)	Table stand included

Specifications

General:	
Dimensions (HxWxD)	410x411x183mm
Mount	VESA standard 100x100mm
Series	eneo Monitor
Housing color	black
Hosuing material	Plastic
Loudspeaker	2
Power consumption	25W
Operating temperature	+5°C ~ +35°C
Weight	2.9kg
Display:	

VM-19PD

Continuation of the specifications

Video standard	PAL/NTSC
Resolution Pixels	1280x1024
Backlighting	LED
Screen size (inch)	19"
Screen size (cm)	48 cm
Aspect ratio	5:4
Viewing angle vertical	160°
Viewing angle horizontal	170°
Brightness typical	250 cd/m²
Contrast ratio typical	2,000,000:1 (DCR)
Reponse time typical	5 ms
Refresh rate	60 Hz
Functions:	
Comb filter	3D comb filter with de-interlace
Menu languages	English, German, Russian, French, Spanish, Dutch, Chinese
Parts supplied:	
Parts supplied	manual, VGA cable, power cord, PSU 100~240VAC
Interfaces / Inputs/ Outputs:	
Audio inputs	RCA jack, 1, 1
Video inputs (type)	composite (CVBS), HDMI, VGA
Video outputs	Composite (CVBS)
Serial interfaces	no
Other	
Display element	Colour TFT/LCD
Special features	Anti-Burn-in Technology
Manufacturer order number	212466

