

MPD-62M2713P0A

SKU: 217279



1/2.8" HD Dome Fixed, WDR, Day&Night,
2.7-13,5mm, Infrare 1920x1080, 12VDC, Indoor

Main Features

1/2.8" 2 Megapixel SONY STARVIS 2 CMOS sensor	Motorized vari-focal lens 2.7~13.5mm
Super low light performance by Sony STARVIS 2 technology	Removable infrared cut filter
Resolution max. 1920x1080 pixels (Full HD)	ROI (Region of Interest) WDR mode
Separate outputs for digital and multi-signal	Integrated motion detector, defog, privacy zones
Multisignal: HD-TVI, AHD, CVI and Composite selectable	Wedge adapter included (10° inclination)
Digital signal: EX-SDI, HD-SDI selectable	Scratch resistant hard coated bubble

Specifications

General:	
Dimensions (HxWxD)	100x116mm
Illumination	2x High Power LEDs 850nm,40°,Infrared
Text display	supplied
Series	eneo Callisto Indoor, eneo KX-Series
Housing	Indoor
Color (housing)	white
Color (bubble)	clear
Housing material	Plastic
Heater	no
Mounting	Ceiling mount, Wall mount

MPD-62M2713P0A

Continuation of the specifications

Supply voltage	12VDC
Power consumption	7W
Vandal proof	no
Operating temperature	-10°C ~ +50°C
Illumination range	approx. 30m
Weight	260g
DORI:	
Observe (62 px/m)	18 - 52 m
Recognize (125 px/m)	8 - 25 m
Identify (250 px/m)	4 - 12 m
Detect (25px/m)	47 - 128 m
Functions:	
Motion detector	yes
OSD function control	OSD camera setup
Menu languages	German,English,Chinese,Japanese,Korean
Mirror function	mirror,V flip
Privacy zone masking	Areas-ON/OFF switchable
Vertical tilt range	65 °(25 ~ 90°)
Digital Noise Reduction	yes
Rotation range	+/-165°
Analysis functions	Defog
Camera:	
Imager	Sony STARVIS,Sony IMX291,CMOS
Automatic electronic shutter (ESC)	1/25 ~ 1/30.000sec.
Flickerless function	yes
Backlight compensation	BLC,HLC
Low speed shutter	yes
Manual electronic shutter (MES)	1/25 ~ 1/30.000sec
Signal-to-noise ratio	50dB
Day&Night mode	Automatic,Day,Night
White balance	Automatic,Preset,Manual
Wide Dynamic Range (WDR)	Real Time WDR 25/30fps,WDR 113dB
System	True Day&Night
Sensor size	1/2.8"
Day&Night switch	ICR
Sensitivity	0,08 Lux at F1,4, 40 IRE
Camera type	Dome
Parts supplied:	
Parts supplied	manual,drilling template,bag of screws
Lens:	
Lens Type	Varifocal (motorized)
Focal Length	2,8 - 12 mm

MPD-62M2713P0A

Continuation of the specifications

Iris Control	DC
Zoom Factor	4x
Digital Zoom	no
MOD (Minimum Object Distance)	0,5 m
Aperture range (F)	F1.4
Interfaces / Inputs/ Outputs:	
External connectors	voltage input, 1x SDI Signal (BNC), 1x HD/SD Analog Signal (BNC), connection cable approx. 15cm
Serial interfaces protocols	UTC (HD-Signal Format)
Video outputs	AHD, Composite (CVBS), CVI, EX-SDI, HD-SDI, HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Video:	
Synchronization	internal
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, EX-SDI (270 Mbps), HD-SDI (1.485 Gbps), HD-TVI @ 2MP
Frame rate	25/30fps @ 1920x1080p, 50/60fps @ 1280x720p
Other	
Remarks	NDAA compliance under Section 889
Video standard	PAL/NTSC
Resolution Pixels	1280x720, 1920x1080, 720x576
Horizontal Angle of View	100 - 38°
Vertical Angle of View	53 - 19°
Manufacturer order number	217279

Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

