

MPC-52C0000M0A

SKU: 217280



1/2.8" HD Camera, Day&Night, 1920x1080, WDR, C/CS, 12/24V

Abb. ähnlich|The lens ist not part of the delivery

Main Features

- 1/2.8" 2 Megapixel SONY STARVIS 2 CMOS sensor
- Super low light performance by STARVIS 2 sensor
- Resolution max. 1920x1080 pixels (Full HD)
- Separate outputs for digital and multi-signal
- Multisignal: HD-TVI, AHD, CVI and Composite selectable

- Digital signal: EX-SDI, HD-SDI selectable
- Removable infrared cut filter
- ROI (Region of Interest) WDR mode
- Integrated motion detector, defog, privacy zones
- C/CS mount, LSC (Lens shading compensation)

Specifications

General:	
Dimensions (HxWxD)	72x74x89mm
Text display	supplied
Series	eneo COAXIZE, eneo KX-Series
Housing	Indoor
Color (housing)	Pantone Cool Gray 1C
Housing material	Aluminium
Supply voltage	12VDC, 24VAC
Power consumption	5W
Operating temperature	-10°C ~ +50°C
Weight	290g
Functions:	

MPC-52C0000M0A

Continuation of the specifications

Motion detector	yes
OSD function control	OSD camera setup
Menu languages	German,English,Chinese,Japanese,Korean
Mirror function	mirror,V flip
Privacy zone masking	Areas-ON/OFF switchable
Digital Noise Reduction	yes
Analysis functions	Defog
Camera:	
Imager	Sony STARVIS,Sony IMX291,CMOS
Automatic electronic shutter (ESC)	1/25 ~ 1/30.000sec.
Flickerless function	yes
Backlight compensation	BLC,HLC
Low speed shutter	yes
Manual electronic shutter (MES)	1/25 ~ 1/30.000sec
Signal-to-noise ratio	50dB
Day&Night mode	Automatic,Day,Night
White balance	Automatic,Preset,Manual
Wide Dynamic Range (WDR)	Real Time WDR 25/30fps,WDR 113dB
System	True Day&Night
Sensor size	1/2.8"
Day&Night switch	ICR
Sensitivity	0,08 Lux at F1,4, 40 IRE
Camera type	Box
Parts supplied:	
Parts supplied	manual,C/CS adapter
Lens:	
Iris Control	DC
Interfaces / Inputs/ Outputs:	
External connectors	voltage input,1x SDI Signal (BNC),1x HD/SD Analog Signal (BNC)
Serial interfaces protocols	UTC (HD-Signal Format)
Video outputs	AHD, Composite (CVBS), CVI, EX-SDI, HD-SDI, HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Video:	
Synchronization	internal
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, EX-SDI (270 Mbps), HD-SDI (1.485 Gbps), HD-TVI @ 2MP
Frame rate	25/30fps @ 1920x1080p, 50/60fps @ 1280x720p
Other	

MPC-52C0000M0A

Continuation of the specifications

Remarks	NDAA compliance under Section 889
Video standard	PAL/NTSC
Resolution Pixels	1280x720, 1920x1080, 720x576
Manufacturer order number	217280

Optional Accessory

SKU	Name	Description
213619	H04Z03NFDC-MP	F1,5/4-13mm, Megapixel DC-Lens, variable Focal Length, 1/1.8" CS-Mount
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive
219504	WD-30	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

