

eneo MPC-52C0000M0A

SKU: 217280



1/2.8" HD Camera, Day&Night, 1920x1080, WDR, C/CS, 12/24V

Camera not included|The lens ist not part of the delivery

Main Features

1/2.8" 2 Megapixel SONY STARVIS CMOS sensor

Resolution max. 1920x1080 pixels (Full HD)

Separate outputs for digital and multi-signal

Multisignal: HD-TVI, AHD, CVI and Composite selectable

Digital signal: EX-SDI, HD-SDI selectable

Removable infrared cut filter

ROI (Region of Interest) WDR mode

Integrated motion detector, defog, privacy zones

C/CS mount, LSC (Lens shading compensation)

Specifications

| General | |
|-------------------------------|----------------------|
| Dimensions (WxHxD) (extended) | 72x74x89mm |
| Weight | 0.29 kg |
| Text overlay | available |
| Color (Housing) | Pantone Cool Gray 1C |
| Housing type | Inside |
| Housing material | Aluminium |
| Power consumption | 5 W |
| Power supply | 12VDC, 24VAC |
| Temperature Range (Operating) | -10°C ~ +50°C |
| Wide Dynamic Range (WDR) | WDR 113dB |
| Camera | |

eneo MPC-52C0000M0A

Continuation of the specifications

| | |
|-------------------------------|--|
| Backlight compensation | Yes |
| Low Speed Shutter | Yes |
| Recording sensor | CMOS |
| Chip size | 1/2,8" |
| Flickerless function | Yes |
| Camera shape | Box |
| Signal-to-noise ratio | 50 dB |
| Day/night mode | Automatic, Day, Night |
| White balance | Automatic, Preset, Manual |
| Photosensitivity | 0,08 Lux bei F1,4,40 IRE |
| System | True Day&Night |
| Day/night switching | Switchable IR Filter (ICR) |
| Display | |
| Image resolution max. | 1920x1080 |
| Functions | |
| Motion detector | Yes |
| Digital Noise Reduction (DNR) | Yes |
| Menu languages | Chinese, English, German, Japanese, Korean |
| Notes | |
| Remark | NDAA compliance under Section 889 |
| Interfaces / Inputs/ Outputs | |
| Alarm inputs | 0 |
| Number of alarm outputs | 0 |
| External connections | voltage input, 1x SDI Signal (BNC), 1x HD/SD Analog Signal (BNC) |
| Interface Protocols | UTC (HD Signal Format) |
| Control Interfaces | Coaxitron (HD Protocol) |
| Video Outputs | AHD, Composite (FBAS), CVI |
| Parts supplied | |
| Scope of delivery | manual, C/CS adapter |
| Video | |
| Resolution (extended) | 1920x1080, 1280x720, 720x576 |
| Signal Format | AHD @ 2MP, Composite (FBAS), CVI @ 2MP, EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP |
| Product labeling: | |
| Manufacturer order number | 217280 |
| Series | eneo KX-Serie, eneo COAXIZE |

Optional Accessory

| SKU | Name | Description |
|--------|--------------------|--|
| 213619 | eneo H04Z03NFDC-MP | F1,5/4-13mm, Megapixel DC-Lens, variable Focal Length, 1/1.8" CS-Mount |

eneo MPC-52C0000M0A

Continuation of accessory

| | | |
|--------|---------------------|--|
| 225085 | eneo MAM-5DC1004M0A | Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output |
| 220299 | eneo MAM-5MM1001M0A | Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor |
| 212984 | eneo TVA-1201TRA | UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V |
| 212985 | eneo TVA-1201TRP | UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive |
| 219504 | eneo WD-30 | Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C |



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

