

eneo ISD-55P0010P0A

SKU: 217871



1/1.8" Network Dome, Fixed, Day&Night, 2592x1944, 360°, H.264, 1.05mm, Indoor

Main Features

1/1.8" Sony STARVIS CMOS-Sensor

1.05mm fixed lens FishEye camera

360° Panorama view

Integration in eneo Center Software

True Day&Night

Resolution max. 2048x1536@15fps

Compression H.264/MJPEG, Web Casting

Cross Web-Browsing

D-WDR (Digital Wide Dynamic Range)

Framerate increase on motion detection

OpenVPN support

Compact design for indoor application

Specifications

General	
Heating	No
Lighting	No
Dimensions (WxHxD) (extended)	63,8x119mm
Weight	0.27 kg
SDK	upon request
Text overlay	available
Color (Housing)	white
Housing type	Inside
Housing material	Plastic
Camera Type	Fisheye Camera

eneo ISD-55P0010P0A

Continuation of the specifications

Power consumption	5.3 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S
Power over Ethernet	IEEE 802.3af
Power supply	12VDC, Poe
Temperature Range (Operating)	-10°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	No
Resolution standard	5 MP
Recording sensor	CMOS
Chip size	1/1,8"
Camera shape	Minsters
Day/night mode	Automatic, Day, Night
White balance	Automatic, fluorescent, Outdoor, Manual, Light bulb
Photosensitivity	0,3 Lux bei F2,8
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (62px/m)	14 m
Detect (125px/m)	6 m
Identify (250px/m)	4 m
Perceiving (25px/m)	36 m
Functions	
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card), E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out
Audio	2 Way Audio
Browser	Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited
Menu languages	Chinese, English, French, German, Japanese, Korean, Russian
Internal memory	microSDHC card, microSDXC card
Notes	
Remark	To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combination, eneo cannot guarantee functionality. If combined use is necessary, we offer a compatibility check

eneo ISD-55P0010P0A

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	Alarm output,Alarm input,Audio input/output,RJ-45,12VDC input (DC plug),connection cable approx.40cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	360°
Vertical angle of view	360°
Focal length	1,05 mm
Lens Type	Prime lens
Zoom Factor (Digital)	0
Video	
Image transfer rate max.	15 fps
Resolution (extended)	2592x1944 (4:3),2048x1536 (4:3),1944x1944,1440x1440,1280x1024 (5:4),1280x960 (4:3),1024x1024,1024x768 (4:3),720x720,704x576 (4:3),640x480 (4:3)
Data stream types	2x H.264, 1x MJPEG simultan
Video Compression	H.264, M-JPEG
Product labeling:	
Manufacturer order number	217871
Series	eneo SN-Serie



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

