

ISD-55P0010P0A

SKU: 217871



1/1.8" Network Dome, Fixed, Day&Night, 2592x1944, 360°, H.264, 1.05mm, Indoor

Main Features

1/1.8" Sony STARVIS CMOS-Sensor	Compression H.264/MJPEG, Web Casting
1.05mm fixed lens FishEye camera	Cross Web-Browsing
360° Panorama view	D-WDR (Digital Wide Dynamic Range)
Integration in eneo Center Software	Framerate increase on motion detection
True Day&Night	OpenVPN support
Resolution max. 2048x1536@15fps	Compact design for indoor application

Specifications

General:	
Dimensions (HxWxD)	63,8x119mm
Illumination	no
SDK	upon request
Text display	supplied
Series	eneo SN-Series
Camera Type	Fisheye Kamera
Housing	Indoor
Color (housing)	white
Hosuing material	Plastic
Heater	no

ISD-55P0010P0A

Continuation of the specifications

Blower	no
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	5.3W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-10°C ~ +50°C
ONVIF	ONVIF Profile S
Weight	270g
DORI:	
Observe (62 px/m)	14 m
Recognize (125 px/m)	6 m
Identify (250 px/m)	4 m
Detect (25px/m)	36 m
Functions:	
Alarm processing	recording internal storage (SD card),E-Mail,FTP,Boost,HTTP,TCP,UDP,HTTPS,XML,alarm out
User interface	Type B (white / blue)
Motion detector	yes
Menu languages	English,German,French,Russian,Chinese,Korean,Japanese
Mirror function	H-flip,mirror
Multicast compliant	yes
Password protection	yes
Privacy zone masking	Areas-ON/OFF switchable
Web browser	MS internet Explorer: ActiveX ex 9.0,Safari: MJPEG setup limited,Mozilla: MJPEG setup limited,Google: MJPEG setup limited,Edge: MJPEG setup limited
Digital Noise Reduction	yes
Audio support	yes
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Tampering protection
Audio	2 Way Audio
Remote configuration	Browser
Notes:	
Remarks	To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combination, eneo cannot guarantee functionality. If combined use is necessary, we offer a compatibility check for a fee (for more information, see article number #229235 at VIDEOR).
Special features	ImmerVision certificate

ISD-55P0010P0A

Continuation of the specifications

Camera:	
Imager	Sony STARVIS,CMOS
Automatic electronic shutter (ESC)	1~1/10.000sec.
Backlight compensation	BLC,HLC
Low speed shutter	no
Manual electronic shutter (MES)	1~1/10000Sek.
Day&Night mode	Automatic,Day,Night
White balance	Automatic,fluorescent,Outdoor,Manual,Light bulb
Wide Dynamic Range (WDR)	D-WDR
Resolution Standard	5 Megapixel
System	True Day&Night
Sensor size	1/1.8"
Day&Night switch	ICR
Sensitivity	0,3 Lux at F2,8
Camera type	Dome
Parts supplied:	
Parts supplied	manual,bag of screws
Network:	
Network protocols	TCP/IP,UDP,IPv4,IPv6,HTTP,HTTPS,FTP,UPnP,RT P,RTSP,RTCP,DHCP,ARP,Zeroconf,Bonjour,QoS
Lens:	
Lens Type	fixed focal length
Focal Length	1,05 mm
Digital Zoom	yes
Interfaces / Inputs/ Outputs:	
External connectors	Alarm output,Alarm input,Audio input/output,RJ-45,12VDC input (DC plug),connection cable approx.40cm
Alarm inputs	1
Alarm outputs	1
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Video:	
Resolution	2592x1944 (4:3),2048x1536 (4:3),1944x1944,1440x1440,1280x1024 (5:4),1280x960 (4:3),1024x1024,1024x768 (4:3),720x720,704x576 (4:3),640x480 (4:3)
Image display	4:3,16:9,5:4
Stream types	2x H.264, 1x MJPEG multiple
Video compression	H.264, M-JPEG
Image resolution max.	2592x1944
Image Transmission Rate	15 fps
Other	

ISD-55P0010P0A

Continuation of the specifications

Horizontal Angle of View	360°
Vertical Angle of View	360°
Manufacturer order number	217871

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

