

VM-HD15P

SKU: 217912



15" (38cm) LCD Monitor HD, 1024x768, LED, HDMI, VGA, Composite

Abb. ähnlich

Main Features

Professional 15" (38 cm) LCD monitor

Industrial design built to run 24x7x365 continuously

Maximum resolution 1024x768 pixels

LED Back Light

Fast response time 5ms

Perfect presentation through digital 3D filtering and noise reduction

Different video inputs HDMI, VGA, Composite

Supply voltage: 12VDC

Plastic cabinet including stand

Kunststoffgehäuse inklusive Standfuß

Specifications

General:	
Dimensions (HxWxD)	274x348,8x42,8mm
Mount	VESA standard 75x75mm
Series	eneo Monitor
Housing color	black
Housing material	Plastic
Loudspeaker	2
Supply voltage	12VDC
Power consumption	11.5W
Operating temperature	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Weight	2.9kg
Display:	

VM-HD15P

Continuation of the specifications

Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Resolution Pixels	1024x768
Backlighting	LED
Screen size (inch)	15"
Screen size (cm)	38 cm
Aspect ratio	4:3
Viewing angle vertical	178°
Viewing angle horizontal	178°
Brightness typical	350 cd/m ²
Contrast ratio typical	700:1
Reponse time typical	5 ms
Refresh rate	60 Hz
Functions:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Parts supplied:	
Parts supplied	manual,power cord,PSU 100~240VAC,IR remote controller,VGA cable,feet
Interfaces / Inputs/ Outputs:	
Audio inputs	1x 3.5mm jack, 1, 1
Video inputs	HDMI 1.4a,HDCP 2.2,HDCP 1.4
Video inputs (type)	2x composite (CVBS), HDMI, VGA
Video outputs	Composite (CVBS)
Serial interfaces	no
Audio output	1x 3,5mm jack
Video:	
Resolution	1024x768 ,800x600,720x400
Other	
Display element	Colour TFT/LCD,Anti-Glare-Display,Hard coating (3H),Haze :25%
Manufacturer order number	217912

Optional Accessory

SKU	Name	Description
224229	VM-LCDWMB2	Wall bracket for LCD monitors horizontal adjustable, support up to max. 8 kg
228560	VM-TSHA	Monitor stand high adjustable up to 130mm, for LCD-Monitors, 15-27 Inch, maximum 10Kg



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

