eneo VM-UHD55M

SKU: 217921



Similar as above image

55" (140cm) LCD Monitor, 4K UHD, 3840x2160, LED, USB, DisplayPort, HDMI, DVI, VGA

Main Features

Professional 55"(140cm) LCD monitor	Built to run 24x7x365 continuously
Maximum resolution 4K UHD 3840x2160 pixels	Different video inputs DisplayPort, HDMI, DVI, VGA
Media player integrated (USB)	Built-in speakers
LED Back Light	Including stand
Perfect presentation through digital 3D filtering and noise reduction	Metal housing (suitable for industrial use)

Specifications

General	
Weight	32 kg
Housing material	Metal
Power consumption	120 W
Display	_headline, Anti-glare display, Color TFT-LCD, Hard coating (3H)
Display element	Colour TFT/LCD,Anti-Glare-Display,Hard coating (3H),Haze :1%
Viewing Angle Horizontal	178 °
Viewing Angle Vertical	178 °
Screen diagonal (cm)	140 cm
Screen diagonal (inches)	55 "
Brightness (typical)	350 cd/m²

© Copyright eneo by VIDEOR E. Hartig GmbH, November 3, 2026 -Technical changes reserved

eneo VM-UHD55M

Continuation of the specifications

Backlight	LED
Contrast ratio (typical)	1100:1
Response time (typical)	5 ms
Aspect ratio	16:9
Refresh rate	30 Hz
Functions	
Menu languages	English
Interfaces / Inputs/ Outputs	
Audio Inputs	1
Transmission Technology	HDCP 1.4, HDCP 2.2, HDMI 1.4b
Control Interfaces	no
Video Inputs	Composite (FBAS), DisplayPort, DVI, HDMI, USB2.0, VGA
Parts supplied	
Scope of delivery	manual,IR remote controller,power cord,feet set,HDMI cable
Video	
Maximum Image Resolution (H x V)	3840x2160
Product labeling:	
Manufacturer order number	217921
Series	eneo Monitor

© Copyright eneo by VIDEOR E. Hartig GmbH, November 3, 2026 -Technical changes reserved