eneo IAM-5SE1004MUC

SKU: 220212

Gigabit Switch, Unmanaged, 4x PoE, 2x RJ45 and 2x SFP, 1000Mbps, Industrial Design

Main Features

- Gigabit PoE switch, DIN Rail
- Gigabit Uplink ports 2xRJ45, 2xSFP
- 4x 10/100/1000 PoE Ports,IEEE 802.3af/at
- Surge protection IEC61000-4-5 (6KV)
- Status LED: Uplink, PoE, Optical port, Power
- Temperature range -40° C ~ +75° C

Specifications

General	
Number of PoE ports	4
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	46x110x163mm
Application environment	inside
Weight	530 kg
Type	Unmanaged
Mounting type	DIN Rail, Wall
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC
Temperature Range (Operating)	-40°C ~ +75°C
Notes	
Remark	External power supply specification: 100~240VAC,150W,30x70x150mm,-30°~+70°

© Copyright eneo by VIDEOR E. Hartig GmbH, June 5, 2026 -Technical changes reserved

eneo IAM-5SE1004MUC

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	2x 10/100/1000Base-TX, 2x 10/100/1000T SFP, 4x 10/100/1000Base-T
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
Internal Switching Capacity (Gbit)	14 Gbps
Internal Switching Capacity (MP per second)	10.4 Mpps
Product labeling:	
Manufacturer order number	220212
Series	eneo Switch

© Copyright eneo by VIDEOR E. Hartig GmbH, June 5, 2026 -Technical changes reserved