

IAM-5SE1004MUC

SKU: 220212



Gigabit Switch, Unmanaged, 4x PoE, 2x RJ45 and 2x SFP, 1000Mbps, Industrial Design

Main Features

Gigabit PoE switch, DIN Rail

Gigabit Uplink ports 2xRJ45, 2xSFP

4x 10/100/1000 PoE Ports, IEEE 802.3af/at

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

Temperature range -40° C ~ +75° C

Specifications

General:	
Dimensions (HxWxD)	46x110x163mm
Construction	DIN rail module
Application	indoor
Type	Unmanaged
Series	eneo Switch
Mounting	DIN rail, wall mount
Blower	no
PoE ports (number)	4
Management	no
Supply voltage	48~57 VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	120 W
Operating temperature	-40°C ~ +75°C
Weight	530g

IAM-5SE1004MUC

Continuation of the specifications

Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Notes:	
Remarks	External power supply specification: 100~240VAC, 150W, 30x70x150mm, -30°~+70°
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU
Network:	
Internal switching capacity (Gbit/s)	14 Gbps
Internal switching capacity (Mpps)	10,4 Mpps
Ethernet standards	IEEE 802.3 10BaseT,IEEE 802.3u 100BaseTX,IEEE 802.ab 1000BaseT,IEEE 802.3z 1000BaseSX/LX,IEEE 802.3at Power Over Ethernet (PoE+),IEEE 802.3af Power Over Ethernet (PoE)
VLAN	no
Interfaces / Inputs/ Outputs:	
Optical connector	SFP Port
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	2x 10/100/1000Base-TX, 2x 10/100/1000T SFP, 4x 10/100/1000Base-T
Other	
Manufacturer order number	220212

Optional Accessory

SKU	Name	Description
219525	RJT-1000SFP	RJ45- SFP Transceiver Modul, 1000Base-T, 0°~+70°C
216479	SFP-0850M10	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1,25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1,25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1,25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

