

IAD-5SE1008MUA

SKU: 220593



Switch, Unmanaged, 120W 8x PoE, 2 x RJ45 Uplink
10/100/1000 Mbps, Desktop

Main Features

Ethernet PoE Switch, desktop application

Gigabit Uplink Ports: 2 x RJ45

8 x 10/100 PoE Ports IEEE 802.3af/at

Up to 30W per Port, Total $\leq 120W$

Surge protection IEC61000-4-5 (6KV)

CCTV mode allows transmission up to 250m @ 10Mbps

Plug and Play no further settings necessary

Specifications

Functions:	
Port mirror	no
QoS	no
SNMP	no
Security	CCTV Mode
Network:	
Ethernet standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	4,2 Mpps
Internal switching capacity (Gbit/s)	5,6 Gbps
VLAN	no
Interfaces / Inputs/ Outputs:	

IAD-5SE1008MUA

Continuation of the specifications

Ethernet interface	10Base-T,100Base-TX,1000Base-T
Ports	8x 10/100Base-TX,2x 10/100/1000Base-T
Optical connector	none
General:	
Dimensions (HxWxD)	27x200x101,8mm
Weight	500g
PoE ports (number)	8
Model	Desktop
Type	Unmanaged
Blower	no
Management	no
Mounting	desktop
PoE budget	120 W
Power over Ethernet	IEEE 802.3af,IEEE 802.3at
Supply voltage	48~57 VDC
Operating temperature	-10°C ~ +55°C
Parts supplied:	
Parts supplied	manual,PSU
Notes:	
Remarks	CCTV mode: transmission of 10Mbps @ 250m,CCTV mode, PoE Power output: 29.2W @ 1m; 25.8W @ 100m; 24.2W @ 150m; 19.9W @ 250m



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

