

eneo IAD-5SE1008MUA

SKU: 220593



Switch, Unmanaged, 120W 8x PoE, 2 x RJ45 Uplink
10/100/1000 Mbps, Desktop

Main Features

Ethernet PoE Switch, desktop application

Gigabit Uplink Ports: 2 x RJ45

8 x 10/100 PoE Ports IEEE 802.3af/at

Up to 30W per Port, Total $\leq 120W$

Surge protection IEC61000-4-5 (6KV)

CCTV mode allows transmission up to 250m @ 10Mbps

Plug and Play no further settings necessary

Specifications

General	
Number of PoE ports	8
Design	Desktop
Dimensions (WxHxD) (extended)	27x200x101,8mm
Weight	500 kg
Type	Unmanaged
Mounting type	Desktop
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC
Temperature Range (Operating)	-10°C ~ +55°C
Notes	
Remark	CCTV mode: transmission of 10Mbps @ 250m, CCTV mode, PoE Power output: 29.2W @ 1m; 25.8W @ 100m; 24.2W @ 150m; 19.9W @ 250m

eneo IAD-5SE1008MUA

Continuation of the specifications

Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	2x 10/100/1000Base-T, 8x 10/100Base-TX
Parts supplied	
Scope of delivery	manual,PSU
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
Security	CCTV mode
Internal Switching Capacity (Gbit)	5.6 Gbps
Internal Switching Capacity (MP per second)	4.2 Mpps
Product labeling:	
Manufacturer order number	220593
Series	eneo Switch



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

