

IAD-5SE1008MUA

SKU: 220593



Switch, Unmanaged, 120W 8x PoE, 2 x RJ45 Uplink
10/100/1000 Mbps, Desktop

Main Features

Ethernet PoE Switch, desktop application	Surge protection IEC61000-4-5 (6KV)
Gigabit Uplink Ports: 2 x RJ45	CCTV mode allows transmission up to 250m @ 10Mbps
8 x 10/100 PoE Ports IEEE 802.3af/at	Plug and Play no further settings necessary
Up to 30W per Port, Total ≤120W	

Specifications

General:	
Dimensions (HxWxD)	27x200x101,8mm
Construction	Desktop
Type	Unmanaged
Series	eneo Switch
Mounting	desktop
Blower	no
PoE ports (number)	8
Management	no
Supply voltage	48~57 VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	120 W
Operating temperature	-10°C ~ +55°C
Weight	500g

IAD-5SE1008MUA

Continuation of the specifications

Functions:	
Port mirror	no
QoS	no
Security	CCTV Mode
SNMP	no
Notes:	
Remarks	CCTV mode: transmission of 10Mbps @ 250m, CCTV mode, PoE Power output: 29.2W @ 1m; 25.8W @ 100m; 24.2W @ 150m; 19.9W @ 250m
Parts supplied:	
Parts supplied	manual, PSU
Network:	
Internal switching capacity (Gbit/s)	5,6 Gbps
Internal switching capacity (Mpps)	4,2 Mpps
Ethernet standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
VLAN	no
Interfaces / Inputs/ Outputs:	
Optical connector	none
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	2x 10/100/1000Base-T, 8x 10/100Base-TX
Other	
Manufacturer order number	220593



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

