

eneo IPD-78M3611M0A

SKU: 220930



1/2,5" Network Dome, Fix, 3840x2160, Day&Night, DOL-WDR 3,6-11mm, Infrared, IP67

Main Features

1/2.5" Sony STARVIS CMOS sensor
Resolution max. 3840x2160, 8 Megapixel
Motorised varifocal lens 3,6~11mm
DOL-WDR (120dB) by triple scan images at 30/25fps
VCA video analysis, ONVIF event mapping
Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of interest)
Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Slot for Micro SD Card, HTML5 replay, Audio, Alarm
Power supply PoE, 12VDC or 24VAC
For outdoor use IP66, vandal proofed IK10
Supports ONVIF Profile S and Profile T

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	119x140mm
Weight	1 kg
SDK	upon request
Text overlay	available
Color (Housing)	Pantone Cool Gray 1C
Color (dome)	clear
Housing type	Inside, Outside

eneo IPD-78M3611M0A

Continuation of the specifications

Housing material	Aluminium
Power consumption	10.8 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67
Power supply	12VDC, 24VAC, Poe
Temperature Range (Operating)	-50°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
Certifications	IK10
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	8 MP
Recording sensor	CMOS
Chip size	1/2,5"
Flickerless function	Yes
Camera shape	Minsters
Signal-to-noise ratio	50 dB
Day/night mode	Automatic, Day, Night, night-color mode, extern (Sensor)
White balance	ATW-Indoor, ATW-Outdoor, Manual, Fluorescent light, Light bulb, Shade, Clear Sky, Flammes
Photosensitivity	0,2 Lux bei F1,5,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	3840x2160
DORI	
Watch (62px/m)	36,6 - 86,5 m
Detect (125px/m)	17,7 - 42,6 m
Identify (250px/m)	8,6 - 21,2 m
Perceiving (25px/m)	91,7 - 214 m
Functions	
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Analysis	Motion Detection
Turning range	173 °
Alarm processing	recording internal storage (SD card), E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping, alarm out

eneo IPD-78M3611M0A

Continuation of the specifications

Audio	2 Way Audio
Browser	Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG
Menu languages	English, French, German, Korean
Password	Administrator and User
Vertical tilt range	65 °(25 ~ 90°)
Internal memory	microSDHC card, microSDXC card
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	micro SD card slot,Alarm in/output,RJ-45,Combi connector,connection cable approx.15cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	84 - 40°
Vertical angle of view	46 - 21°
Focal length	3,6 - 11 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	3
Video	
Image transfer rate max.	30 fps
Resolution (extended)	3840x2160 (16:9),2592x1520 (16:9),1920x1080 (16:9),1600x900 (16:9),1280x720 (16:9),960x540 (16:9),640x360 (16:9),320x180 (16:9)
Data stream types	Multi-Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	220930
Series	eneo LN-Serie

Optional Accessory

SKU	Name	Description
209832	eneo AK-5	Camera Junction Box, for Callisto Dome series, IP66
216923	eneo DOME-S1	Sun Shield for eneo Callisto Dome Series
215644	eneo DOME-WB3	Wall bracket for eneo Dome Cameras MED-62xxxxxM0A and IED-62xxxxxM0A
209831	eneo DOME/BASIS1	Surface mount base , Callisto Dome line
207192	eneo DOME/WEDGE2	Wedge Adapter, Callisto Dome Line
221334	eneo IAM-4MU1001M0A	EPOC Signal Converter, BNC to 2-wire cable transmission for EPOC Cameras, Transceiver

eneo IPD-78M3611M0A

Continuation of accessory

218218	eneo Site Manager	Management Software for eneo IP products
--------	-------------------	--



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

