IAM-6MC1001M0A

SKU: 221273

Ethernet over Coax Transceiver Data/Power supply 270Mbps, 57VDC power input

Main Features

EPOC Ethernet and Power over Coax Transmission	Power Output 12VDC/2A (with optional power supply 221276)
RJ45 Ethernet and BNC-Female plug	128 Bit AES Network Encryption
Max. Transmission Rate 270Mbps Full Duplex	Supports Multi Connection (Daisy Chain, Star)
Data Transmission up to 2.4Km	Surge Protection
Transmission PoC up to 1.2Km	Temperature Range (Operating) -20° C bis +60°C
Power Supply Transceiver 57V DC	Easy Installation (Plug & Play)

Specifications

General:	
Dimensions (HxWxD)	28x83x132mm
Construction	module
Series	eneo EPOC, eneo Switch
Housing	Metal
Color	anthracite
Supply voltage	56VDC, Power over Coax (PoC)
Operating temperature	-20°C ~ +60°C
Weight	200g
Network:	
Data tranfer rate max.	270 Mbps

© Copyright eneo by VIDEOR E. Hartig GmbH, April 2024 -Technical changes reserved

IAM-6MC1001M0A

Continuation of the specifications

Interfaces / Inputs/ Outputs:	
External connectors	RJ-45,BNC - EPOC,56VDC input (DC plug),12VDC / 2A Poweroutput
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Other	
Special features	Network transmission with 128bit AES encryption standard
Parts supplied	manual
Model	module
Manufacturer order number	221273

Optional Accessory

SKU	Name	Description
221334	IAM-4MU1001M0A	EPOC Signalkonverter, BNC auf Zweidraht Übertragung, Zubehör für EPOC Kameras, Transceiver
221276	NE-141/220VAC-57VDC	Netzteil Eingang 100-240VAC, Ausgang 57VDC 1,2A, für EPOC Transceiver, Transmitter, Rec.

© Copyright eneo by VIDEOR E. Hartig GmbH, April 2024 -Technical changes reserved