

# IAM-6MC1001MRA

SKU: 221577



Ethernet Coax Receiver Data & Power over Coax 1 x RJ-45, 1 x BNC

## Main Features

EPOC Ethernet and Power over Coax Transmission

RJ45 Ethernet and BNC-Female plug

Max. Transmission Rate 95Mbps Full Duplex

Data Transmission up to 2.4Km

PoC Transmission up to 1.2Km

Power Supply Receiver PoE or 12-57V DC

PoE/PoE+ Power Supply for Transmitter

128 Bit AES Network Encryption

Supports Multi Connection (Daisy Chain, Star)

Surge Protection

Temperature Range (Operating) -20° C bis +60°C

Easy Installation (Plug & Play)

## Specifications

General:	
Dimensions (HxWxD)	24x61,6x82,4mm
Construction	module
Series	eneo EPOC
Housing	Metal
Color	anthracite
Supply voltage	56VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Operating temperature	-20°C ~ +60°C
Weight	77g
Network:	

# IAM-6MC1001MRA

Continuation of the specifications

Data transfer rate max.	95 Mbps
Interfaces / Inputs/ Outputs:	
External connectors	RJ-45,BNC - EPOC (max. 60W out),56VDC input (DC plug)
Ethernet interface	100Base-TX, 10Base-T
Other	
Special features	Network transmission with 128bit AES encryption standard
Parts supplied	manual
Manufacturer order number	221577

## Optional Accessory

SKU	Name	Description
221334	IAM-4MU1001M0A	EPOC Signalkonverter, BNC auf Zweidraht Übertragung, Zubehör für EPOC Kameras, Transceiver
221276	NE-141/220VAC-57VDC	Netzteil Eingang 100-240VAC, Ausgang 57VDC 1,2A, für EPOC Transceiver, Transmitter, Rec.



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

