

IAM-6MC1001MRA

SKU: 221577



Ethernet Coax Receiver Data & Power over Coax 1 x RJ-45, 1 x BNC

Main Features

EPOC Ethernet and Power over Coax Transmission

RJ45 Ethernet and BNC-Female plug

Max. Transmission Rate 95Mbps Full Duplex

Data Transmission up to 2.4Km

PoC Transmission up to 1.2Km

Power Supply Receiver PoE or 12-57V DC

PoE/PoE+ Power Supply for Transmitter

128 Bit AES Network Encryption

Supports Multi Connection (Daisy Chain, Star)

Surge Protection

Temperature Range (Operating) -20° C bis +60°C

Easy Installation (Plug & Play)

Specifications

| | |
|-----------------------|----------------------------|
| General: | |
| Dimensions (HxWxD) | 24x61,6x82,4mm |
| Construction | module |
| Series | eneo EPOC |
| Housing | Metal |
| Color | anthracite |
| Supply voltage | 56VDC |
| Power over Ethernet | IEEE 802.3af, IEEE 802.3at |
| Operating temperature | -20°C ~ +60°C |
| Weight | 77g |
| Network: | |

IAM-6MC1001MRA

Continuation of the specifications

| | |
|-------------------------------|--|
| Data transfer rate max. | 95 Mbps |
| Interfaces / Inputs/ Outputs: | |
| External connectors | RJ-45,BNC - EPOC (max. 60W out),56VDC input (DC plug) |
| Ethernet interface | 100Base-TX, 10Base-T |
| Other | |
| Special features | Network transmission with 128bit AES encryption standard |
| Parts supplied | manual |
| Manufacturer order number | 221577 |

Optional Accessory

| SKU | Name | Description |
|--------|---------------------|--|
| 221334 | IAM-4MU1001M0A | EPOC Signalkonverter, BNC auf Zweidraht Übertragung, Zubehör für EPOC Kameras, Transceiver |
| 221276 | NE-141/220VAC-57VDC | Netzteil Eingang 100-240VAC, Ausgang 57VDC 1,2A, für EPOC Transceiver, Transmitter, Rec. |



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

