

# IAD-5SG1004MUB

SKU: 221888



Gigabit Switch, Unmanaged, 60W, 4x PoE, 2x RJ45  
10/100/1000 Mbps, Desktop

## Main Features

Gigabit PoE switch, desktop application

4x 10/100/1000 PoE Ports, IEEE 802.3ab/af/at/u

Gigabit Uplink Ports: 2 x RJ45

Up to 30W per Port, Total  $\leq 60W$

Surge protection IEC61000-4-5 (6KV)

CCTV mode allows transmission up to 250m @ 10Mbps

Plug and Play no further settings necessary

## Specifications

Series	Safe & Easy
Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Security	CCTV Mode
Network:	
Ethernet standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	8,9 Mpps
Internal switching capacity (Gbit/s)	12 Gbps

# IAD-5SG1004MUB

Continuation of the specifications

VLAN	no
Interfaces / Inputs/ Outputs:	
Ethernet interface	10Base-T,100Base-TX,1000Base-T
Ports	4x 10/100/1000Base-T (PoE),2x 10/100/1000Base-T
General:	
Dimensions (HxWxD)	27x135x86mm
Weight	350g
PoE ports (number)	4
Model	Desktop
Type	Unmanaged
Power consumption	60W
Blower	no
Management	no
Mounting	desktop
PoE budget	60 W
Power over Ethernet	IEEE 802.3af,IEEE 802.3at
Supply voltage	48~57 VDC
Operating temperature	-10°C ~ +45°C
Application	indoor
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

