

IAM-5SE1004MUP

SKU: 221889



Gigabit Switch, Unmanaged 60W, 4x PoE, Industrial Design -40°C~+75°C, PD port

Main Features

Gigabit PoE Switch, DIN Rail

4x 10/100/1000 PoE Ports, IEEE 802.3ab/af/at/u

Gigabit Uplink Ports 1xRJ45, 1xSFP

1 x RJ45 10/100/1000 PoE In Port (60W PoE Input)

Up to 30W per port, total max. 120W

PoE watchdog (reboot automatically)

Surge protection IEC61000-4-5 (6KV)

Temperature range -40° C ~ +75° C

Specifications

Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Network:	
Ethernet standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	8,9 Mpps
Internal switching capacity (Gbit/s)	12 Gbps
VLAN	yes
Interfaces / Inputs/ Outputs:	

IAM-5SE1004MUP

Continuation of the specifications

Ethernet interface	10Base-T,100Base-TX,1000Base-T
Ports	4x 10/100/1000Base-T,1x 1000Base-X SFP,1x 10/100/1000Base-T (PoE-PD)
General:	
Dimensions (HxWxD)	46x110x163mm
Weight	540g
PoE ports (number)	4
Model	DIN rail module
Type	Unmanaged
Power consumption	60W
Blower	no
Management	no
Mounting	DIN rail
PoE budget	60 W
Power over Ethernet	IEEE 802.3af,IEEE 802.3at
Supply voltage	48~57 VDC,PoE
Operating temperature	-40°C ~ +75°C
Application	indoor
Trunk	Contact discharge 6KV,Air discharge 8KV,IEC61000-4-2,IEC 61000-6-2
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU
Notes:	
Remarks	We recommend the use edp. number: 216568 PoE Injector NE-60PoE to ensure an interference-free function with power supply via PD port

Optional Accessory

SKU	Name	Description
216568	NE-60PoE	PoE Injector, 60W, for Switch IAD-5SG1004MUA and IAM-5SE1004MUP
219525	RJT-1000SFP	RJ45- SFP Transceiver Modul, 1000Base-T, 0°~+70°C
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

IAM-5SE1004MUP

Continuation of accessory



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

