

IAM-5SE1004MUP

SKU: 221889



Gigabit Switch, Unmanaged 60W, 4x PoE, Industrial Design -40°C~+75°C, PD port

Main Features

Gigabit PoE Switch, DIN Rail	PoE watchdog (reboot automatically)
4x 10/100/1000 PoE Ports, IEEE 802.3ab/af/at/u	Surge protection IEC61000-4-5 (6KV)
1 x SFP Gigabit uplink port	Temperature range -40° C ~ +75° C
1 x RJ45 Gigabit uplink port, PD-capable (60W PoE input)	Temperaturbereich -40°C ~ +75°C

Specifications

General:	
Dimensions (HxWxD)	46x110x163mm
Construction	DIN rail module
Application	indoor
Trunk	Contact discharge 6KV,Air discharge 8KV,IEC61000-4-2,IEC 61000-6-2
Type	Unmanaged
Series	eneo Switch
Mounting	DIN rail
Blower	no
PoE ports (number)	4
Management	no
Supply voltage	48~57 VDC, PoE
Power consumption	60W

IAM-5SE1004MUP

Continuation of the specifications

Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	60 W
Operating temperature	-40°C ~ +75°C
Weight	540g
Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Notes:	
Remarks	We recommend the use edp. number: 216568 PoE Injector NE-60PoE to ensure an interference-free function with power supply via PD port
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU
Network:	
Internal switching capacity (Gbit/s)	12 Gbps
Internal switching capacity (Mpps)	8,9 Mpps
Ethernet standards	IEEE 802.3 10BaseT,IEEE 802.3u 100BaseTX,IEEE 802.ab 1000BaseT,IEEE 802.3x Flow Control,IEEE 802.3at Power Over Ethernet (PoE+),IEEE 802.3af Power Over Ethernet (PoE)
VLAN	yes
Interfaces / Inputs/ Outputs:	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T (PoE-PD), 1x 1000Base-X SFP, 4x 10/100/1000Base-T
Other	
Manufacturer order number	221889

Optional Accessory

SKU	Name	Description
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

IAM-5SE1004MUP

Continuation of accessory



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone:
Fax:
E-Mail:
Web:

+49 6074 - 888 - 300
+49 6074 - 888 - 100
info@eneo-security.com
www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

