

TSD-52F0013P0A

SKU: 221916



1/3" HD Dome, Fixed, Day&Night 1920x1080, Infrared, 1,34mm, 360°, Indoor, 12VDC

Main Features

1/1,3" Progressive CMOS-Sensor	D-WDR (Digital Wide Dynamic Range)
1,34mm fixed focal length	UTC support remote control by Pelco C protocol
HD-TVI analouge fishEye camera	For ceiling and wall installation
360° surround and 180° panorama view	Compact design for indoor application
Resolution max. 1920x1080@25fps	

Specifications

General:	
Dimensions (HxWxD)	33,5x77mm
Illumination	4x IR LED 850nm,Infrared
Series	EX-Series
Camera Type	Fisheye Kamera
Housing	Indoor
Color (housing)	white
Color (bubble)	clear
Housing material	Plastic
Heater	no
Blower	no
Mounting	Ceiling mount, Wall mount

TSD-52F0013P0A

Continuation of the specifications

Supply voltage	12VDC
Power consumption	3.2W
Vandal proof	no
Operating temperature	0°C ~ +40°C
Illumination range	approx. 7m
Weight	345g
Functions:	
Motion detector	no
Menu languages	English
Mirror function	V flip,H-flip,H/V flip
Privacy zone masking	no
Digital Noise Reduction	yes
Camera:	
Imager	Progressive scan,CMOS, CMOS
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.
Low speed shutter	no
Signal-to-noise ratio	50dB
Day&Night mode	Automatic,Day,Night
White balance	Automatic,Push lock
Wide Dynamic Range (WDR)	D-WDR, D-WDR
System	True Day&Night
Sensor size	1/3"
Day&Night switch	ICR
Sensitivity	0,5 Lux at F2,0, 30 IRE
Camera type	Dome
Parts supplied:	
Parts supplied	manual,drilling template,screw set
Lens:	
Lens Type	fixed focal length
Focal Length	1,34 mm
Digital Zoom	no
MOD (Mininum Object Distance)	0,3 m
Aperture range (F)	F2.0
Interfaces / Inputs/ Outputs:	
External connectors	12VDC input (DC plug),1x HD Analog Signal (BNC),connection cable approx.40cm
Serial interfaces protocols	UTC (HD-Signal Format)
Video outputs	HD-TVI
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Video:	

TSD-52F0013P0A

Continuation of the specifications

Signal format	HD-TVI @ 2MP
Frame rate	25/30fps @ 1920x1080p
Other	
Video standard	PAL/NTSC
Resolution Pixels	1920x1080
Low Speed Shutter	no
Motion Detector	no
Horizontal Angle of View	360°
Illumination	Infrared
Manufacturer order number	221916

Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive

TSD-52F0013P0A

Technical Drawing



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone:
Fax:
E-Mail:
Web:

+49 6074 - 888 - 300
+49 6074 - 888 - 100
info@eneo-security.com
www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

