

eneo IPP-62A0020M0B

SKU: 222184



1/2,8" Network Dome, PTZ, Day&Night, 20x, H.265, WDR, 1920x1080, PoE, IP66

Main Features

1/2.8" Sony STARVIS CMOS-Sensor	Digital Noise Reduction (2DNR/3DNR)
Full HD 1920x1080 Pixel, 25/30fps	Audio support including audio alarm
23x AF Zoom, 4.7~94mm	Alarm in- and outputs, micro SD-card slot
Quad Stream H.265, H.264, MJPEG (Smart Codec)	Power supply 12VDC, 24VAC or PoE
Real time WDR (Wide Dynamic Range) 25/30fps	IK10 IK shock resistance degree
Intelligent motion detector	Support ONVIF Profile S und Profile T

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	No
Dimensions (WxHxD) (extended)	150x154mm
Weight	1.6 kg
SDK	upon request
Text overlay	available
Color (Housing)	white
Color (dome)	clear
Housing type	Inside, Outside

eneo IPP-62A0020M0B

Continuation of the specifications

Housing material	Aluminium
Power consumption	12 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP66
Power supply	12VDC, 24VAC, Poe
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	WDR 120dB
Certifications	IK10
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	2 MP
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	PTZ
Signal-to-noise ratio	50 dB
Day/night mode	Day,Night,Automatic
White balance	Automatic,Manual
Photosensitivity	0,2 Lux bei F1,6,50 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	30,2 - 591,6 m
Detect (125px/m)	14,7 - 292,6 m
Identify (250px/m)	7 - 146 m
Perceiving (25px/m)	75,7 - 1446,5 m
Functions	
Analysis	Intrusion (PID), Manipulation (TD), Motion Detection
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Turning range	360 °
Alarm processing	recording internal storage (SD card),E-Mail,FTP,Boost,HTTP,TCP,UDP,HTTPS,XML,alarm out
Audio	2 Way Audio
Browser	Edge: MJPEG setup limited, Google Chrome: MJPEG setup limited, Mozilla: MJPEG setup limited, Safari: MJPEG setup limited

eneo IPP-62A0020M0B

Continuation of the specifications

Home Position	Selectable, Tour, Preset, Pattern
Menu languages	Chinese, English, French, German, Japanese, Korean, Russian
Password	Administrator and User
Tours	8 selectable tours
Vertical tilt range	-10° ~ 190°
Speed (manual control)	380 °/sec
Speed (Target Approach)	380 °/sec
Internal memory	microSDHC card, microSDXC card
Notes	
Remark	To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combination, eneo cannot guarantee functionality. If combined use is necessary, we offer a compatibility check
Interfaces / Inputs/ Outputs	
Alarm inputs	4
External connections	Alarm output, Alarm input, Audio in/output, RJ-45, voltage input, connection cable approx. 25cm
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual, plug set, bag of screws
Lens	
Horizontal angle of view	55,5 - 3°
Vertical angle of view	32,4 - 1,7°
Focal length	4,7 - 94 mm
MOD (Minimum Object Distance)	1 m
Lens Type	Auto Focus Zoom
Zoom Factor (Digital)	16
Zoomfactor (optical)	20
Video	
Image transfer rate max.	30 fps
Resolution (extended)	1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3),
Data stream types	Quad Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	222184
Series	eneo SN-Serie



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

