

AES-5SF0036M1A

SKU: 223916



1/3" Mini Dome, Fix, clear, 3,6mm, 960TVL, 12VDC, vandalism protect

Main Features

1/3" Fix dome camera with Sony CCD	White-coloured aluminium die-cast casing
Integrated lens F2.0/3.6mm	Clear Lexan bubble, 57mm
Resolution of 960 horizontal lines	Easy indoor installation
Automatic shutter control	For wall or ceiling mounting
Digital signal processing (DSP)	Vandal resistant
Automatic white balance (ATW)	

Specifications

General:	
Dimensions (HxWxD)	60,5x80
Illumination	no
Series	eneo COAXIZE
Housing	Outdoor
Color (housing)	white
Color (bubble)	clear
Housing material	Aluminium
Heater	no
Mounting	Ceiling mount
Supply voltage	12VDC

AES-5SF0036M1A

Continuation of the specifications

Power consumption	1.2W
Vandal proof	yes
Operating temperature	-10°C ~ +50°C
Certifications	IK10
Protection rating	IP66
Weight	260g
DORI:	
Observe (62 px/m)	12,6 m
Recognize (125 px/m)	5,9 m
Identify (250 px/m)	2,8 m
Detect (25px/m)	32,2 m
Functions:	
Motion detector	no
e-PTZ support	no
Digital Noise Reduction	yes
Camera:	
Imager	Sony Super HAD II Interline Transfer, CCD, CCD
Automatic electronic shutter (ESC)	1/50 ~ 1/120,000sec.
Backlight compensation	BLC
Low speed shutter	no
Manual electronic shutter (MES)	1/50 ~ 1/120,000sec.
Signal-to-noise ratio	-50 db
Day&Night mode	Automatic
White balance	ATW
Wide Dynamic Range (WDR)	no, no
System	electronic Day&Night
Sensor size	1/3"
Day&Night switch	Electronic
Sensitivity	0,1 Lux at F1,2, 50 IRE
Camera type	Dome
Parts supplied:	
Parts supplied	manual, screw set, bag of screws
Lens:	
Lens Type	fixed focal length
Focal Length	3,6 mm
Digital Zoom	no
MOD (Minimum Object Distance)	0,1 m
Interfaces / Inputs/ Outputs:	
External connectors	12VDC input (DC plug), Composite (FBAS), connection cable approx. 25cm
Video outputs	Composite (CVBS)
Alarm inputs	no

AES-5SF0036M1A

Continuation of the specifications

Alarm outputs	no
Serial interfaces	no
Video:	
Synchronization	internal
Horizontal resolution	960 TVL
Other	
Active picture elements	976(H) x 582(V) pixels
Video standard	PAL
Low Speed Shutter	no
Backlight Compensation	BLC
Motion Detector	no
Horizontal Angle of View	68°
Illumination	no
Manufacturer order number	223916

Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
236125	MAM-5MM2203M0A	Converter, 4K HD-TVI, HD-CVI, AHD, auf HDMI, Indoor 12VDC
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

