ICB-65M2713M5A

SKU: 227051



1/2,8" Network Camera, 2592x1944, Day&Night, DOL-WDR, 2,7-13,5mm, Infrared, IP67

Main Features

1/2.8" Sony STARVIS CMOS sensor	Smart Codec H.265 ROI (Region of interest) HTML5 playback
Resolution max. 2592x1944, 5 Megapixel	Quad Smart Streaming: H.265(+), H.264(+), MJPEG
Motorised varifocal lens 2,7~13.5mm	Micro SD Card, HTML5 replay, Audio, Alarm
DOL-WDR (120dB) by triple scan images at 30/25fps	Power supply PoE IEEE 802.3af
VCA video content analysis, ONVIF event mapping	Integrated connection box including connection board
Browser independent (IE, Edge, Safari, Firefox, Chrome)	Supports ONVIF Profile S and Profile T

Specifications

General:	
Dimensions (HxWxD)	130,50x82,15x265,80mm
Illumination	4x High Power LED 850nm,Infrared
Integrated wall mount	yes
SDK	upon request
Sunshield	yes
Supply voltage	PoE, PoE
Text display	supplied
Series	eneo Candid Small, eneo LN-Series
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C

© Copyright eneo by VIDEOR E. Hartig GmbH, March 2024 -Technical changes reserved

ICB-65M2713M5A

Continuation of the specifications

Hosuing material	Aluminium
Blower	yes
Mounting	Ceiling mount, Wall mount
Power consumption	9,2W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-50°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Protection rating	IP67
Illumination range	approx. 40m
Weight	1.25kg
DORI:	
Observe (62 px/m)	32,5 - 105,4 m
Recognize (125 px/m)	15,3 - 52 m
Identify (250 px/m)	6,4 - 25,7 m
Detect (25px/m)	84 - 262,7 m
Functions:	
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping,alarm out
User interface	Type A (orange / grey)
Motion detector	yes
Digital noise reduction (DNR)	yes
e-PTZ support	yes
Menu languages	English,German,French,Korean
Mirror function	mirror,flip
Multicast compliant	yes
Password protection	administrator & users
Privacy zone masking	Areas-ON/OFF switchable
Web browser	MS internet Explorer: ActiveX ex 9.0,Safari: MJPEG,Mozilla: MJPEG,Google Chrome: MJPEG,Edge: MJPEG
Audio support	yes
Internal storage	microSDHC card, microSDXC card
Analysis functions	Defog, Field detection, Line detection, Motion detection, Object left,removed
Audio	2 Way Audio
Remote configuration	Browser
Notes:	
Special features	Integrated connection box with sabotage alarm contact,Simple wiring, the integrated connection board offers the possibility of network cabling via LSA connection bar or RJ45 socket.Terminal block for connection of alarm contacts and audio.

© Copyright eneo by VIDEOR E. Hartig GmbH, March 2024 -Technical changes reserved

ICB-65M2713M5A

Continuation of the specifications

Camera:	
Imager	Sony STARVIS,Sensor IMX335,CMOS, CMOS
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.
Flickerless function	yes
Backlight compensation	BLC,HLC
Low speed shutter	1x~10x,yes
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.
Signal-to-noise ratio	50dB
Day&Night mode	Automatic,Day,Night,night-color mode,extern (Sensor)
White balance	ATW-Indoor,ATW-Outdoor,Manual,Fluorescent light,Light bulb,Shade,Clear Sky,Flammes
Wide Dynamic Range (WDR)	D-WDR, D-WDR, DOL-WDR 120dB
Resolution Standard	5 Megapixel
System	True Day&Night
Sensor size	1/2.8"
Day&Night switch	ICR
Sensitivity	0,05 Lux at F1,6, 40 IRE
Camera type	Bullet
Parts supplied:	
Parts supplied	manual,bag of screws
Network:	
Network protocols	TCP/IP,UDP,IPv4,IPv6,HTTP,HTTPS,FTP,UPnP,RTP,RTSP,RTCP,DHCP,ARP,Zeroconf,Bonjour
Lens:	
Iris control	DC
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Zoom Factor	4x
Digital Zoom	yes
MOD (Mininum Object Distance)	0,5 m
Interfaces / Inputs/ Outputs:	
External connectors	micro SD card slot,Connection board (LSA, RJ45, audio, I / O alarm & Sabotage contacts)
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Video:	
Resolution	2592x1944 (4:3),2592x1520 (16:9),2560x1440 (16:9),1920x1080 (16:9),1600x900 (16:9),1280x720 (16:9),960x540 (16:9),640x360 (16:9),320x180 (16:9)

© Copyright eneo by VIDEOR E. Hartig GmbH, March 2024 -Technical changes reserved

ICB-65M2713M5A

Continuation of the specifications

Image display	VerticalView 90°/270°,4:3,16:9
Stream types	Multi Streaming
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	2560x1944
Image Transmission Rate	30 fps
Other	
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Motion Detector	yes
Objektiv Typ	Varifocal (motorized)
Iris Control	DC
Horizontal Angle of View	97 - 29°
Vertical Angle of View	54 - 17°
Ilumination	Infrared
Manufacturer order number	227051


Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4

© Copyright eneo by VIDEOR E. Hartig GmbH, March 2024 -Technical changes reserved

ICB-65M2713M5A

Technical Drawing



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe to the eneo newsletter

© Copyright eneo by VIDEOR E. Hartig GmbH, March 2024 -Technical changes reserved