

eneo IAM-5SE1008MUB

SKU: 228223



Gigabit Switch, 8xPoE 100Mbps, 1x RJ45, 1x SFP
1000Mbps, Unmanaged, Industrial Design

Main Features

Gigabit PoE switch, DIN Rail

Gigabit Uplink ports 1xRJ45, 1xSFP

8x 10/100 PoE Ports, IEEE 802.3af/at

Up to 30W per port

Surge protection IEC61000-4-5 (6KV)

Status LED: Uplink, PoE, Optical port, Power

PoE reset button for each port

CCTV mode allows transmission up to 250m @ 10Mbps

Temperature range -40° C ~ +75° C

Specifications

General	
Number of PoE ports	8
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	46,5x163x110,5mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	530 kg
Type	Unmanaged
Mounting type	DIN Rail, Wall
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	48-57 VDC

eneo IAM-5SE1008MUB

Continuation of the specifications

Temperature Range (Operating)	-40°C ~ +75°C
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-TX, 1x 10/100/1000T SFP, 8x 10/100Base-TX
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
VLAN	Yes
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
Internal Switching Capacity (Gbit)	5.6 Gbps
Internal Switching Capacity (MP per second)	4.2 Mpps
Product labeling:	
Manufacturer order number	228223
Series	eneo Switch

Optional Accessory

SKU	Name	Description
218758	eneo SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	eneo SFP-1310M40	SFP Modul, 1,25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	eneo SFP-1310S10	SFP Modul, 1,25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

