

IAM-5SE1004MUD

SKU: 228224



Switch, Unmanaged, 120W, 4xPoE 1x RJ45, 1x SFP
100Mbps, Industrial Design, -40°C~+75°C

Main Features

Ethernet PoE Switch, DIN Rail	Surge protection IEC61000-4-5 (6KV)
Uplink ports 1xRJ45, 1xSFP	Status LED: Uplink, PoE, Optical port, Power
4x 10/100 PoE Ports,IEEE 802.3af/at	CCTV mode allows transmission up to 250m @ 10Mbps
Up to 30W per port	Temperature range -40° C ~ +75° C

Specifications

General:	
Dimensions (HxWxD)	46x110x159mm
Construction	DIN rail module
Application	indoor
Trunk	Contact discharge 6KV,Air discharge 8KV,IEC61000-4-2,IEC61000-4-5
Type	Unmanaged
Series	eneo Switch
Mounting	DIN rail, wall mount
Blower	no
PoE ports (number)	4
Management	no
Supply voltage	48~57 VDC
Power over Ethernet	IEEE 802.3af, IEEE 802.3at

IAM-5SE1004MUD

Continuation of the specifications

PoE budget	120 W
Operating temperature	-40°C ~ +75°C
Weight	530g
Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
Security	CCTV Mode
SNMP	no
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU
Network:	
Internal switching capacity (Gbit/s)	1,5 Gbps
Internal switching capacity (Mpps)	0,9 Mpps
Ethernet standards	IEEE 802.3 10BaseT,IEEE 802.3u 100BaseTX,IEEE 802.3at Power Over Ethernet (PoE+),IEEE 802.3af Power Over Ethernet (PoE)
VLAN	no
Interfaces / Inputs/ Outputs:	
Optical connector	SFP Port
Ethernet interface	100Base-TX, 10Base-T
Ports	1x 10/100Base-TX, 1x 100 SFP, 4x 10/100Base-TX
Other	
Manufacturer order number	228224

Optional Accessory

SKU	Name	Description
216567	SFP-0850MM10	SFP Modul, 155Mbps , 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

