

IPD-42M2713PAA

SKU: 230799



1/2,8" Network Dome, Fix, 1920x1080, Day/Night, DOL-WDR 2,7-13,5mm, Infrared, Indoor

Main Features

1/2.8" Sony STARVIS CMOS Sensor	Browser independent (IE, Edge, Safari, Firefox, Chrome)
Excellent light sensitivity	Smart Codec H.265 ROI (Region of Interest)
Resolution max. 1920x1080 (Full HD)	Supports ONVIF Profile S and Profile T
Motorised varifocal lens 2.7~13.5mm	Vertical View 90°/270° Modus,H-Flip, Mirror
DOL-WDR (120dB) by triple scan images at 30/25fps	Compact Fix Dome Housing (plastic) for indoor
Motion Detection, Privacy Zones, Slow Shutter	Power supply PoE or 12VDC

Specifications

General:	
Dimensions (HxWxD)	87x113mm
Illumination	4x High Power LED 850nm,Infrared
SDK	upon request
Text display	supplied
Series	eneo AN-Series
Housing	Indoor
Color (housing)	white
Housing material	ABS plastic
Window heater	no
Blower	yes

IPD-42M2713PAA

Continuation of the specifications

Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC, PoE
Power consumption	12VDC, 7.5W, PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-10°C ~ +50°C
ONVIF	ONVIF Profile S, ONVIF Profile T
Illumination range	approx. 30m
Weight	270g
DORI:	
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Detect (25px/m)	44 - 198 m
Functions:	
Alarm processing	E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping
User interface	Type A (orange / grey)
Motion detector	yes
e-PTZ support	yes
Menu languages	English,German,French,Korean
Mirror function	mirror,flip
Multicast compliant	yes
Password protection	administrator & users
Privacy zone masking	Areas-ON/OFF switchable
Web browser	MS internet Explorer: ActiveX ex 9.0,Safari: MJPEG,Mozilla: MJPEG,Google Chrome: MJPEG,Edge: MJPEG
Digital Noise Reduction	yes
Audio support	no
Internal storage	no
Analysis functions	Motion detection, Tampering Detection (TD)
Remote configuration	Browser
Notes:	
Remarks	NDAA compliance under Section 889,To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combination, eneo cannot guarantee functionality. If combined use is necessary, we offer a compatibility check for a fee (for more information, see article number #229235 at VIDEOR).
Camera:	
Imager	Sony STARVIS,Sensor IMX307,CMOS, CMOS

IPD-42M2713PAA

Continuation of the specifications

Automatic electronic shutter (ESC)	1/25 ~ 1/25.000sec
Flickerless function	yes
Backlight compensation	BLC,HLC
Low speed shutter	yes
Manual electronic shutter (MES)	1/25 ~ 1/25.000sec
Signal-to-noise ratio	50dB
Day&Night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Outdoor,Light bulb,Fluorescent light,Clear Sky,Shade,Manual
Wide Dynamic Range (WDR)	D-WDR, D-WDR, DOL-WDR 120dB
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Day&Night switch	ICR
Sensitivity	0,0008 Lux at F1,6, 40 IRE
Camera type	Dome
Parts supplied:	
Parts supplied	manual,bag of screws
Network:	
Network protocols	TCP/IP,UDP,IPv4,IPv6,HTTP,HTTPS,FTP,UPnP,RT P,RTSP,RTCP,DHCP,ARP,Zeroconf,Bonjour,SNMP
Lens:	
Lens Type	Varifocal (motorized)
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	yes
MOD (Mininum Object Distance)	0,5 m
Interfaces / Inputs/ Outputs:	
External connectors	12VDC input (DC plug),RJ-45
Video outputs	no
Alarm inputs	no
Alarm outputs	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Video:	
Resolution	1920x1080 (16:9),1280x720 (16:9)
Image display	VerticalView 90°/270°,16:9
Stream types	Multi Streaming
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps

IPD-42M2713PAA

Continuation of the specifications

Other	
Low Speed Shutter	yes
Backlight Compensation	BLC, HLC
Motion Detector	yes
Horizontal Angle of View	108 - 32°
Vertical Angle of View	56 - 18°
Illumination	Infrared
Manufacturer order number	230799



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

