

IPB-62M2713MAA

SKU: 232571



1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 2.7-13.5mm, Infrared, IP66

Abb. ähnlich

Main Features

1/2.8" Sony STARVIS CMOS Sensor

Excellent light sensitivity

Resolution max. 1920x1080 (Full HD)

Motorised varifocal lens 2.7~13.5mm

DOL-WDR (120dB) by triple scan images at 30/25fps

Motion Detection, Privacy Zones, Slow Shutter

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of Interest)

Supports ONVIF Profile S and Profile T

Vertical View 90°/270° Modus, H-Flip, Mirror

Bullet Housing (metal), IP66

Power supply PoE or 12VDC

Specifications

Series	eneo AN-Series
Camera:	
Camera type	Bullet
Sensor size	1/2.8"
Resolution Standard	HD 1080p
Imager	CMOS, Sony STARVIS, Sensor IMX307
System	True Day&Night
Sensitivity	0,0008 Lux, at F1.6, 40IRE
Low Speed Shutter	yes
Manual electronic shutter (MES)	1/25 ~ 1/25.000sec
Automatic electronic shutter (ESC)	1/25 ~ 1/25.000sec

IPB-62M2713MAA

Continuation of the specifications

Wide Dynamic Range (WDR)	DOL-WDR 120dB,D-WDR
Flickerless function	yes
Backlight Compensation	BLC,HLC
Day&Night switch	ICR
Day&Night mode	auto,day,night,extern (Sensor)
White balance	automatic,outdoor,Light bulb,Fluorescent light,Clear Sky,Shade>manual
Signal-to-noise ratio	50dB
Video:	
Resolution	1920x1080 (16:9),1280x720 (16:9)
Image resolution max.	1920x1080
Image display	VerticalView 90°/270°,16:9
Stream types	Multi Streaming
Image Transmission Rate	30 fps
Video compression	H.264,H.264+ (Smart Stream),H.265,H.265+ (Smart Stream),M-JPEG
Lens:	
Lens Type	Varifocal (motorized)
Zoom Factor	4x
Focal Length	2,7 - 13,5 mm
Digital Zoom	yes
MOD (Minimum Object Distance)	0,5 m
Iris Control	DC
Vertical Angle of View	56 - 18°
Horizontal Angle of View	108 - 32°
DORI:	
Detect (25px/m)	44 - 198 m
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Functions:	
Multicast compliant	yes
Motion Detector	yes
Analysis functions	motion detection,tampering protection
Alarm processing	E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping
Audio support	no
Password protection	administrator & users
e-PTZ support	yes
Internal storage	no
Menu languages	English,German,French,Korean
Privacy zone masking	Areas-ON/OFF switchable
Remote configuration	web browser

IPB-62M2713MAA

Continuation of the specifications

Web browser	MS internet Explorer: ActiveX ex 9.0,Safari: MJPEG,Mozilla: MJPEG,Google Chrome: MJPEG,Edge: MJPEG
User interface	Type A (orange / grey)
Mirror function	mirror,flip
Digital Noise Reduction	yes
Network:	
Network protocols	TCP/IP,UDP,IPv4,IPv6,HTTP,HTTPS,FTP,UPnP,RT P,RTSP,RTCP,DHCP,ARP,Zeroconf,Bonjour,SNMP
Interfaces / Inputs/ Outputs:	
Video outputs	no
External connectors	12VDC input (DC plug),RJ-45
Ethernet interface	10Base-T,100Base-TX
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Ethernet
General:	
Dimensions (HxWxD)	78,5x78,5x214mm
Weight	600g
Illumination	infrared
Illumination	4x High Power LEDs 850nm
Illumination range	approx. 40m
Color (housing)	Pantone Cool Gray 1C
Housing	outdoor
Housing material	aluminium
Integrated wall mount	yes
Power consumption	PoE,8W,12VDC,8W
Blower	yes
Mounting	wall mount,ceiling mount
ONVIF	ONVIF Profile S,ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection rating	IP66
SDK	upon request
Sunshield	yes
Supply voltage	PoE,12VDC
Operating temperature	-20°C ~ +50°C
Text display	supplied
Vandal proof	no
Parts supplied:	
Parts supplied	manual,bag of screws
Notes:	
Remarks	NDAA compliance under Section 889, Part A.

Optional Accessory

SKU	Name	Description
-----	------	-------------

IPB-62M2713MAA

Continuation of accessory

230863	AK-10	Camera junction box for wall and ceiling mounting
218218	eneo Site Manager	Management Software for eneo IP products



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

