

# eneo IPB-62M2713M0A

SKU: 232571



Camera not included

1/2.8" Network Camera, 1920x1080, Day/Night, DOL-WDR, 2.7-13.5mm, Infrared, IP66

## Main Features

1/2.8" Sony STARVIS CMOS Sensor

Excellent light sensitivity

Resolution max. 1920x1080 (Full HD)

Motorised varifocal lens 2.7~13.5mm

DOL-WDR (120dB) by triple scan images at 30/25fps

Motion Detection, Privacy Zones, Slow Shutter

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of Interest)

Supports ONVIF Profile S and Profile T

Vertical View 90°/270° Modus, H-Flip, Mirror

Bullet Housing (metal), IP66

Power supply PoE or 12VDC

## Specifications

General	
Sunshade canopy	Yes
Integrated wall mount	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	78,5x78,5x214mm
Weight	0.6 kg
SDK	upon request
Text overlay	available
Color (Housing)	Pantone Cool Gray 1C
Housing type	Outside
Housing material	Aluminium

# eneo IPB-62M2713M0A

## Continuation of the specifications

Power consumption	8 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP66
Power supply	12VDC, Poe
Temperature Range (Operating)	-20°C ~ +50°C
Wide Dynamic Range (WDR)	D-WDR
<b>Camera</b>	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	2 MP
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Bullet
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	Automatic,Outdoor,Light bulb,Fluorescent light,Clear Sky,Shade,Manual
Photosensitivity	0,0008 Lux bei F1,6,40 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
<b>Display</b>	
Image resolution max.	1920x1080
<b>DORI</b>	
Watch (62px/m)	11,6 - 45,6 m
Detect (125px/m)	5,5 - 22,7 m
Identify (250px/m)	3 - 11,2 m
Perceiving (25px/m)	30,3 - 113,9 m
<b>Functions</b>	
Audio support	No
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Analysis	Manipulation (TD), Motion Detection
Alarm processing	E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping
Browser	Edge: MJPEG, Mozilla: MJPEG, Safari: MJPEG
Menu languages	English, French, German, Korean
Password	Administrator and User
<b>Notes</b>	
Remark	NDA compliance under Section 889, To guarantee you an optimum user experience, we recommend that you only use components of the same brand in a system. If several brands are used in combination, eneo cannot guarantee functionality. If combined use is necessary

# eneo IPB-62M2713M0A

## Continuation of the specifications

Interfaces / Inputs/ Outputs	
Alarm inputs	0
External connections	12VDC input (DC plug),RJ-45
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Lens	
Horizontal angle of view	108 - 32°
Vertical angle of view	56 - 18°
Focal length	2,7 - 13,5 mm
MOD (Minimum Object Distance)	0.5 m
Lens Type	Varifocal (motorized)
Zoom Factor (Digital)	0
Zoomfactor (optical)	4
Video	
Image transfer rate max.	30 fps
Resolution (extended)	1920x1080 (16:9),1280x720 (16:9)
Data stream types	Multi-Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
Manufacturer order number	232571
Series	eneo AN-Serie

## Optional Accessory

SKU	Name	Description
230863	eneo AK-10	Camera junction box for wall and ceiling mounting
218218	eneo Site Manager	Management Software for eneo IP products



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

