

MPD-62V2713P0A

SKU: 233014



1/2,8" HD Dome, Fix, Day&Night 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, Indoor

Main Features

1/2.8" 2.3 Megapixel progressive scan CMOS sensor	Removable infrared cut filter
Compact plastic housing for indoor use	3D-DNR noise reduction
Resolution max. 1920x1080 (Full HD)	Digital Wide Dynamic Range (D-WDR)
Multisignal: HD-TVI, AHD, CVI, Composite selectable	Integral motion detection
Variofocal 2.8~12mm day&night lens	Wedge adapter included (10° inclination)
LSC (Lens shading compensation)	Scratch resistant hard coated bubble

Specifications

General:	
Dimensions (HxWxD)	100x116mm
Illumination	2x High Power LEDs 850nm,Infrared
Text display	supplied
Series	eneo KX-Series
Housing	Indoor
Color (housing)	white
Color (bubble)	clear
Housing material	Plastic
Heater	no
Mounting	Ceiling mount, Wall mount

MPD-62V2713P0A

Continuation of the specifications

Supply voltage	12VDC
Power consumption	6W
Vandal proof	no
Operating temperature	-10°C ~ +50°C
Illumination range	approx. 30m
Weight	260g
DORI:	
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Detect (25px/m)	44 - 198 m
Functions:	
Motion detector	yes
OSD function control	OSD camera setup
Menu languages	German,English,French,Italian,Spanish,Turkish,Dutch,Portugese,Polish,Chinese,Russian
Mirror function	rotation,mirror,V flip
Privacy zone masking	Areas-ON/OFF switchable
Vertical tilt range	65 °(25 ~ 90°)
Digital Noise Reduction	yes
Analysis functions	Defog
Camera:	
Imager	Sony,Sensor IMX323,CMOS
Automatic electronic shutter (ESC)	1/25 ~ 1/50.000sec..
Flickerless function	yes
Backlight compensation	BLC,HLC
Low speed shutter	yes
Manual electronic shutter (MES)	1/25 ~ 1/50.000sec.
Signal-to-noise ratio	52db
White balance	ATW,AWB,Manual,Outdoor,Indoor,AWC
Wide Dynamic Range (WDR)	D-WDR
System	True Day&Night
Sensor size	1/2.8"
Day&Night switch	ICR
Sensitivity	0,3 Lux at F1,3, 40 IRE
Camera type	Dome
Parts supplied:	
Parts supplied	manual,screw set,Video sub-out cable,drilling template,bag of screws
Lens:	
Lens Type	Varifocal
Focal Length	2,7 - 13,5 mm
Iris Control	DC

MPD-62V2713P0A

Continuation of the specifications

Zoom Factor	4x
Digital Zoom	no
MOD (Minimum Object Distance)	0,5 m
Aperture range (F)	F1,3
Interfaces / Inputs/ Outputs:	
External connectors	video (BNC),12VDC input (DC plug),connection cable approx. 15cm
Serial interfaces protocols	UTC (HD-Signal Format)
Video outputs	AHD, Composite (CVBS), CVI, HD-TVI
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Video:	
Synchronization	internal
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
Frame rate	25/30fps @ 1920x1080p
Other	
Remarks	NDAA compliance under Section 889
Special features	Exact focus setting aid,Hard Coated Bubble (Hardness grade - H) -- Anti Scratch Protection
Video standard	PAL/NTSC
Resolution Pixels	1920x1080, 960x576
Horizontal Angle of View	95 - 27°
Vertical Angle of View	49 - 15°
Manufacturer order number	233014

Optional Accessory

SKU	Name	Description
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
218653	PS12DC-11	Plug-in Power Supply Unit, 100-240VAC/12VDC (1,0A), regulated, with DC Plug
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

