

MEB-62V2713P0A

SKU: 233016



1/2.8" HD Bullet, Day&Night, 1920x1080, Lens 2,7-13,5mm, IR LED, 12VDC, IP66

Abb. ähnlich

Main Features

1/2.8" 2.3 Megapixel progressive scan CMOS sensor
Compact housing for outdoor use
Resolution max. 1920x1080 (Full HD)
Multisignal: HD-TVI, AHD, CVI, Composite selectable
Variofocal 2.8~12mm day&night lens
LSC (Lens shading compensation)

Removable infrared cut filter
3D-DNR noise reduction
Digital Wide Dynamic Range (D-WDR)
Integral motion detection
4x High Power LED

Specifications

General:	
Dimensions (HxWxD)	78,5x78,5x214mm
Illumination	4x High Power LED 850nm, Infrared
Integrated wall mount	yes
Sunshield	yes
Text display	supplied
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	Aluminium, Plastic
Mounting	Ceiling mount, Wall mount
Supply voltage	12VDC

MEB-62V2713P0A

Continuation of the specifications

Power consumption	6.5W
Operating temperature	-20°C ~ +50°C
Protection rating	IP66
Illumination range	approx. 30m
Weight	520g
DORI:	
Observe (62 px/m)	16,6 - 80,5 m
Recognize (125 px/m)	8,2 - 40,1 m
Identify (250 px/m)	3,9 - 20,1 m
Detect (25px/m)	44 - 198 m
Functions:	
Motion detector	yes
OSD function control	OSD camera setup
Menu languages	German,English,French,Italian,Spanish,Turkish,Dutch,Portugese,Polish,Chinese,Russian
Mirror function	rotation,mirror,V flip
Privacy zone masking	Areas-ON/OFF switchable
Digital Noise Reduction	yes
Analysis functions	Defog
Camera:	
Imager	Sony,Sensor IMX323,CMOS
Automatic electronic shutter (ESC)	1/25 ~ 1/50.000sec..
Flickerless function	yes
Backlight compensation	BLC,HLC
Low speed shutter	yes
Manual electronic shutter (MES)	1/25 ~ 1/50.000sec.
Signal-to-noise ratio	52db
White balance	ATW,AWB,Manual,Outdoor,Indoor,AWC
Wide Dynamic Range (WDR)	D-WDR
System	True Day&Night
Sensor size	1/2.8"
Day&Night switch	ICR
Sensitivity	0,3 Lux at F1,6, 40 IRE
Camera type	Bullet
Parts supplied:	
Parts supplied	manual,drilling template,bag of screws
Lens:	
Lens Type	Varifocal
Focal Length	2,7 - 13,5 mm
Iris Control	DC
Zoom Factor	4x
Digital Zoom	no

MEB-62V2713P0A

Continuation of the specifications

MOD (Minimum Object Distance)	0,5 m
Aperture range (F)	F1.6
Interfaces / Inputs/ Outputs:	
External connectors	video (BNC), 12VDC power input, connection cable approx. 40cm
Serial interfaces protocols	UTC (HD-Signal Format)
Video outputs	AHD, Composite (CVBS), CVI, HD-TVI
Alarm inputs	nein
Alarm outputs	no
Serial interfaces	Coaxitron (HD Protocol)
Video:	
Synchronization	internal
Signal format	AHD @ 2MP, Composite (FBAS), CVI @ 2MP, HD-TVI @ 2MP
Frame rate	25/30fps @ 1920x1080p
Other	
Remarks	NDAA compliance under Section 889
Video standard	PAL/NTSC
Resolution Pixels	1920x1080, 960x576
Horizontal Angle of View	95 - 27°
Vertical Angle of View	49 - 15°
Manufacturer order number	233016

Optional Accessory

SKU	Name	Description
230863	AK-10	Camera junction box for wall and ceiling mounting
225085	MAM-5DC1004M0A	Distributor, 1x BNC Input HD-TVI, CVI, AHD, CVBS, 4x BNC Output
220299	MAM-5MM1001M0A	Converter, HD-CVI, HD-TVI, AHD, Composite to HDMI, VGA, Composite, Indoor
212984	TVA-1201TRA	UTP Transmitter+Receiver, UTP, BNC, 250m, Indoor, HD TVI CVI, AHD, CVBS, Active, 12V
212985	TVA-1201TRP	UTP Transmitter+Receiver, UTP, BNC, 150m, Indoor, HD TVI CVI, AHD, CVBS, Passive



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

