

eneo MPC-52A0030M0A

SKU: 233052



1/3" HD Camera, 1920x1080, 30x AF Zoom
4,3-129mm, T-WDR, HD-SDI, EX-SDI, TVI,
Composite

Main Features

1/3" 2,0 Megapixel Panasonic CMOS-Sensor
Resolution max. 1920x1080, 1080p@60/50fps
Optical 30x Auto Focus Zoom, 4,3~129mm
Multisignal Output HD-SDI, EX-SDI, TVI, Composite
Real time True WDR
Digital Noise Reduction(2D+3D)

Digital Image Stabilization
Privacy Masking, Defog
Slow Speed Shutter
Compact Housing
Power Supply 12VDC

Specifications

General	
Lighting	No
Dimensions (WxHxD) (extended)	74x67x121,5mm
Weight	0.61 kg
Text overlay	available
Color (Housing)	silvermetallic,black
Housing type	Inside
Housing material	Aluminium
Power consumption	6 W
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C

eneo MPC-52A0030M0A

Continuation of the specifications

Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/3"
Flickerless function	Yes
Camera shape	Zoom cameras
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	AUTO,One push,Manual,Indoor,Outdoor
Photosensitivity	0,5 Lux bei F1,6,50 IRE
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080,1280x720
DORI	
Watch (62px/m)	27,8 - 800 m
Detect (125px/m)	12,4 - 400 m
Identify (250px/m)	5,6 - 190 m
Perceiving (25px/m)	70,3 - 1800 m
Functions	
Analysis	Motion Detection
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, Japanese
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
Number of alarm outputs	1
External connections	1x SDI Signal (BNC),1x HD/SD Analog Signal (BNC),12VDC power input,RS-485,external day&night switching,Alarm output
Interface Protocols	Pelco D, Pelco P, UTC (HD Signal Format)
Control Interfaces	Coaxitron (HD Protocol), RS-485
Video Outputs	Composite (FBAS)
Parts supplied	
Scope of delivery	manual
Lens	
Horizontal angle of view	58,9 - 2,11°
Vertical angle of view	45,3 - 1,61°
Focal length	4,3 - 129 mm

eneo MPC-52A0030M0A

Continuation of the specifications

Aperture Range (F)	F1.6~F4.7
Lens Type	Auto Focus Zoom
Zoom Factor (Digital)	0
Zoomfactor (optical)	30
Video	
Signal Format	Composite (FBAS), EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP
Horizontal resolution	700 TVL
Product labeling:	
Manufacturer order number	233052



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

