

eneo MEB-55M2812M0A

SKU: 233697



HD Analogue Camera Bullet, Day&Night, 2592x1944, Infrared 2,7-13,5mm, 12VDC, IP67

Main Features

1/2.8" CMOS Image Sensor

Resolution max. 2592x1944

multi-signal: HD-TVI, AHD, CVI, CVBS

2,7-13,5 mm lens with variable focal length (motorized)

Day/night switching (ICR)

2D+3D DNR (Digital Noise Reduction)

Automatic exposure control (1/30s~1/50,000s)

Lens shading correction

IR LED illumination integrated

For outdoor use degree of protection IP67

12VDC power supply, NDAA compliant

Specifications

General	
Heating	No
Sunshade canopy	Yes
Integrated wall mount	Yes
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	83,88x87,4x242mm
Illumination range	ca. 35m
Weight	0.745 kg
Text overlay	available
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request

eneo MEB-55M2812M0A

Continuation of the specifications

Housing type	Outside
Housing material	Aluminium
Camera Type	Bullet Camera
Power consumption	6.5 W
Mounting type	Ceiling, Wall
Protection	IP67
Power supply	12VDC
Temperature Range (Operating)	-30°C ~ +55°C
Wide Dynamic Range (WDR)	True WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	No
Recording sensor	CMOS, Sony IMX335
Chip size	1/2,8"
Automatic Electronic Shutter (AES)	1/30 ~ 1/50.000sec.
Flickerless function	Yes
Camera shape	Bullet
Manual Electric Shutter (MES)	1-30~1-50,000sec
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night
White balance	Manual,Automatic
Photosensitivity	0,05 Lux bei F1,2
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (62px/m)	15,6 - 72,5 m
Detect (125px/m)	7,5 - 35,5 m
Identify (250px/m)	3,5 - 10,4 m
Perceiving (25px/m)	40 - 179,3 m
Functions	
Motion detector	No
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, French, Italian, Japanese, Polish, Portuguese, Russian, Spanish
Privacy Zone	Bereiche-EIN/AUS schaltbar
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
External connections	12VDC power input,video (BNC)
Control Interfaces	Coaxitron (HD Protocol)

eneo MEB-55M2812M0A

Continuation of the specifications

Video Outputs	AHD, Composite (FBAS)
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,3 wall plugs with screws,1 Allen wrench
Lens	
Horizontal angle of view	110,6 - 32,6°
Vertical angle of view	57,3 - 18,3°
Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.8~F3.3
Lens Type	Varifocal (motorized)
Zoomfactor (optical)	4
Video	
Resolution (extended)	2592x1944,2560x1440,1920x1080,960x540
Signal Format	AHD @ 2MP, AHD @ 4MP, AHD @ 5MP, Composite (FBAS), CVI @ 2MP, CVI @ 4MP, HD-TVI @ 2MP, HD-TVI @ 4MP, HD-TVI @ 5MP
Product labeling:	
EAN/GTIN	4260229840320
Manufacturer order number	233697
Series	eneo COAXIZE

Optional Accessory

SKU	Name	Description
233754	eneo AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
245314	eneo AK-30	Camera junction box for wall- and ceiling mount fix turret dome and bullet cameras IN-Serie
235257	eneo PM-21	Pole mounting adapter, steel for camera connection box AK-20, AK-21 and wall mount WB-24
245272	eneo PM-21	Pole mounting adapter V2A stainless steel, for camera connection box AK-20, AK-21 and wall mount WB-24



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

