eneo MED-65M2812M0A

SKU: 233706



HD Analogue Dome Camera Fix, 2592x1944, Day&Night, 2,7-13,5mm, IR, 12VDC, IP67, IK10

Main Features

- 1/2.8" CMOS Image Sensor
- Resolution max. 2592x1944
- multi-signal: HD-TVI, AHD, CVI, CVBS
- 2,7-13,5 mm lens with variable focal length (motorized)
- Day/night switching (ICR)
- 2D+3D DNR (Digital Noise Reduction)
- Automatic exposure control (1/30s~1/50,000s)
- Lens shading correction
- IR LED illumination integrated
- For outdoor use degree of protection IP67/IK10
- 12VDC power supply, NDAA compliant

Specifications

General	
Heating	No
Vandalism-resistant	Yes
Lighting	Infrared
Dimensions (WxHxD) (extended)	148.0x109.0mm
Illumination range	ca. 35m
Weight	0.875 kg
Text overlay	available
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request
Color (dome)	clear

© Copyright eneo by VIDEOR E. Hartig GmbH, November 2, 2026 -Technical changes reserved

eneo MED-65M2812M0A

Continuation of the specifications

Housing type	Outside
Housing material	Aluminium
Camera Type	Domecamera
Power consumption	6.5 W
Mounting type	Ceiling, Wall
Protection	IP67
Power supply	12VDC
Temperature Range (Operating)	-30°C ~ +55°C
Wide Dynamic Range (WDR)	WDR 120dB
Certifications	IK10
Camera	
Backlight compensation	Yes
Low Speed Shutter	No
Recording sensor	CMOS, Sony IMX335
Chip size	1/2,8"
Automatic Electronic Shutter (AES)	1/30 ~ 1/50.000sec.
Camera shape	Minsters
Manual Electric Shutter (MES)	1-30~1-50,000sec
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night
White balance	Manual,Automatic
Photosensitivity	0,05 Lux bei F1,2
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (62px/m)	24,3 - 104,5 m
Detect (125px/m)	11,5 - 52,2 m
Identify (250px/m)	5,2 - 25,6 m
Perceiving (25px/m)	62,5 - 260,3 m
Functions	
Motion detector	No
Digital Noise Reduction (DNR)	Yes
Turning range	350 °
Menu languages	Chinese, English, French, Italian, Japanese, Polish, Portuguese, Russian, Spanish
Privacy Zone	Areas-ON/OFF switchable
Notes	
Remark	NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
External connections	12VDC power input,video (BNC)

© Copyright eneo by VIDEOR E. Hartig GmbH, November 2, 2026 -Technical changes reserved

eneo MED-65M2812M0A

Continuation of the specifications

Control Interfaces	Coaxitron (HD Protocol)
Video Outputs	AHD, Composite (FBAS)
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,4 wall plugs with screws,1 Torx wrench
Lens	
Horizontal angle of view	110,6 - 32,6°
Vertical angle of view	57,3 - 18,3°
Focal length	2,7 - 13,5 mm
Aperture Range (F)	F1.8~F3.3
Lens Type	Varifocal (motorized)
Zoomfactor (optical)	4
Video	
Resolution (extended)	2592x1944,2560x1440,1920x1080,960x540
Signal Format	AHD @ 2MP, AHD @ 4MP, AHD @ 5MP, Composite (FBAS), CVI @ 2MP, CVI @ 4MP, HD-TVI @ 2MP, HD-TVI @ 4MP, HD-TVI @ 5MP
Product labeling:	
EAN/GTIN	4260229840337
Manufacturer order number	233706
Series	eneo COAXIZE

Optional Accessory

SKU	Name	Description
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
235525	eneo AK-25	Camera junction box for ceiling pipe DOME-CH6 and wall bracket DOME-WB6
235526	eneo AK-26	Camera junction box for wall- and ceiling mount Fix dome cameras IN-Serie
236663	eneo DOME-WB8	Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series
237253	eneo IN-Dome-S2	Sunshield for eneo IN-series Fix Dome IND-62xx, IND-65xx, IND-68xx
239856	eneo IND-FMH2	Ceiling installation adapter with white cover ring for dome cameras IN-Series

© Copyright eneo by VIDEOR E. Hartig GmbH, November 2, 2026 -Technical changes reserved