

eneo INR-28N320005A

SKU: 234750



Network Video Recorder 32x IP total, 16x IP PoE, HDMI, 4xSATA, w/o HDD

Main Features

Maximum resolution 8MP (recording)

Recording and research AI analysis functions

Recording modes continuous, manual or AI-based

Maximum data rate input 256Mbps, output 128Mbps

Various options for alarm messages

Maximum 4 internal hard disk possible

Supports 16 x alarm inputs and 1 x alarm output

3 x USB inputs, 1 x RS-485, 1 x audio input and output

eSATA port for external storage expansion

NetDrive or cloud storage (Google Drive/Dropbox)

Remote access via browser, eneo Insight or Insight mobile

32 IP channels, 16 x RJ45 PoE port (220 Watt PoE budget)

Specifications

System requirements	
Operating system	Linux
General	
Dimensions (WxHxD) (extended)	378x66x327mm
External Eneo Operating Devices	Mouse
Control software	eneo INsight
HDD Slots Number	4, bis zu 10 TB je slot (Enterprise-Class)
Power consumption	12 W
ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Temperature Range (Operating)	0°C ~ +40°C
Recording	

eneo INR-28N320005A

Continuation of the specifications

Resolution Recording (max)	3840x2160
Hard disk capacity max	40 TB
Functions	
Analysis	Depending on connected IP camera
Audio support	Yes
HDD Hotswap	No
Alarm triggers	AI, Contact, Disk Error, Image loss, Movement
Alarm response	Alarm Output, Buzzer, E-mail dispatch, FTP, Live Popup, PTZ Preset, Push (Mobile), Spot Popup
Menu languages	Arabic, Bulgarian, Danish, Dutch, English, Finnish, French, German, Greek, Hebrew, Hindi, Italian, Japanese, Korean, Polish, Portuguese, Romanian, Russian, Spanish, Thai, Turkish
Password	Administrator and User
Search function	Event, Instant playback, Museum, Text, Thumbnail, VCA Search
Remote Access	Android, Ios, Remote Software, WEB Browser (Java)
Notes	
Remark	IP cameras of the PXB,PXC,PXD and PTB series are not supported by this product. NDAA compliance under Section 889
Interfaces / Inputs/ Outputs	
Alarm Input	Yes
Alarm output	Yes
Number of IP Channels	32
Audio Inputs	1
Ethernet interface	1000Base-T, 100Base-T
Memory interface (external)	USB
Control Interfaces	RS-485
Video Outputs	2x HDMI, VGA
Parts supplied	
Scope of delivery	4x HDD assembly-kit,Power cord,mouse,19" rack mount angle>manual
Network	
Data throughput (outbound)	128 Mbps
Data throughput (maximum)	256 Mbps
Network Protocols	DDNS, DHCP, DNA, FTP, HTTP, HTTPS, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
Video	
Video Compression	H.264, H.264+, H.265, H.265+
Product labeling:	
EAN/GTIN	4260229840016
Manufacturer order number	234750
Series	eneo IN-Serie

eneo INR-28N320005A

Continuation of the specifications

Optional Accessory

SKU	Name	Description
234995	eneo INR-eSATA	
234989	eneo INsight	Control software for recorder IN- and MN-series
236197	eneo INsight Evidence Locker	For the research of HDD's for recorders of IN-series
236196	eneo INsight Evidence Player	For replay of exported data for recorder IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products
245574	Western Digital WD44PURZ	WD Purple Hard Drive, 3.5", SATA 6 Gb/s 4TB, 128MB Cache, 24x7, optimized for video surveillance
237767	Western Digital WD64PURZ	WD Purple hard drive, 3.5", SATA 6 Gb/s, 6TB, 256MB Cache, 24x7, optimized for video surveillance
241613	Western Digital WD85PURZ	



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

