

# eneo INP-75A0033MIA

SKU: 234751



Network Dome, PTZ, 33x, 2952x1944, Day & Night, WDR, AI, Alarm, Audio, 24VAC/12VDC, PoE, IP66

## Main Features

- 1/2.7" CMOS sensor, maximum resolution 5 MP/30fps
- AI analysis functions including object classification
- WDR 120dB, 3D-DNR Noise Reduction
- Motorized autofocus zoom lens 33x 4.3-142mm
- Smart Codec H.265/H.264, multi-streaming
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Supports ONVIF Profile S and Profile T
- Local storage via Micro SD card
- Audio input and output
- IR LED illumination, IP66
- Wall bracket included

## Specifications

General	
Heating	No
Lighting	Infrared
Dimensions (WxHxD) (extended)	206,4x351,8mm
Weight	3.7 kg
Color (Housing)	RAL9003,Pantone P 179-1,black
Housing type	Outside
Housing material	Aluminium
Camera Type	Face, People counting, Retail Intelligence
Power consumption	25.5 W
Mounting type	Wall

# eneo INP-75A0033MIA

## Continuation of the specifications

ONVIF	ONVIF Profile G, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3at
Protection	IP66
Power supply	12VDC, PoE+
Temperature Range (Operating)	-30°C ~ +60°C, @ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	5 MP
Recording sensor	CMOS
Chip size	1/2,7"
Flickerless function	Yes
Camera shape	PTZ
Day/night mode	Automatic, Day, Night, Image, Time
White balance	Automatic, Manual
Photosensitivity	0,003 Lux bei F1,6
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	2592x1944
DORI	
Watch (62px/m)	42,5 - 1041 m
Detect (125px/m)	20,5 - 515 m
Identify (250px/m)	10 - 258 m
Perceiving (25px/m)	106 - 2596 m
Functions	
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Analysis	Face Capture (FD), Face Recognition (FR), Heat Map (HM), Line crossing (LCD), Manipulation (TD)
Turning range	360
Alarm processing	recording internal storage (SD card), E-Mail, FTP, Cloud Upload
Audio	2 Way Audio
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Tours	1 selectable tour

# eneo INP-75A0033MIA

## Continuation of the specifications

Speed (manual control)	200 °/sec
Speed (Target Approach)	200 °/sec
Internal memory	microSD card slot
Notes	
Remark	The face recognition functions are only available with an inserted SD card or in conjunction with a recorder of the eneo IN series.,To guarantee you an optimum user experience,we recommend that you only use components of the same brand in a system. If sev
Interfaces / Inputs/ Outputs	
Alarm inputs	0
External connections	RJ-45,Audio input/output,12VDC input (DC plug),connection cable approx.45cm,micro SD card slot 256 GB
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,wall bracket,bag of screws
Lens	
Horizontal angle of view	55 - 2,3°
Vertical angle of view	41,6 - 1,7°
Focal length	4,3 - 142 mm
MOD (Minimum Object Distance)	0 m
Lens Type	Auto Focus Zoom
Zoomfactor (optical)	33
Video	
Image transfer rate max.	30 fps
Resolution (extended)	2592x1944 (4:3),2592x1520 (16:9),2304x1296 (16:9),1920x1080 (16:9),1280x960 (4:3),640x480 (4:3),320x240 (4:3)
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
EAN/GTIN	4260229840160
Manufacturer order number	234751
Series	eneo IN-Serie



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: info@eneo-security.com  
Web: www.eneo-security.com

Stay informed and subscribe  
to the eneo newsletter

