

# eneo INT-8SF0003M0A

SKU: 236317



Network Hybrid Thermal Bullet Camera Day/Night, 2592x1944 optical, 256x192 thermal, IP66, PoE, 12VDC

## Main Features

Dual network bullet camera	Temperature alarm measuring range -20°~ +150° (±8°)
Optical resolution 2592x1944 pixels	Supports audio and alarm inputs and outputs
Thermal resolution 256x192 pixels	Local storage via micro SD card
Fixed focal 3.6mm (optical) H:81°, V:57°	Supports ONVIF profiles S/T/G/M
Fixed focal 3.2mm (thermal) H:56°, V:42°	NDAA compliance
AI analysis functions including object classification (optical)	Suitable for outdoor use IP66

## Specifications

General	
Heating	No
Sunshade canopy	Yes
Integrated wall mount	Yes
Vandalism-resistant	No
Lighting	Infrared, Warm Light
ESC	1/25 ~ 1/25.000Sek.
Weight	1.45 kg
Text overlay	Switchable on/off
Color (Housing)	RAL9003, Other colors available upon request
Housing type	Outside

# eneo INT-8SF0003M0A

## Continuation of the specifications

Housing material	Aluminium
Camera Type	Thermal Hybrid Bullet
Power consumption	18.2 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Power supply	12VDC, Poe
Temperature Range (Operating)	-30°C ~ +60°C
Thermal resolution	256x192
Wide Dynamic Range (WDR)	WDR 120dB
<b>Camera</b>	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Manual Electric Shutter (MES)	1-25~1-25,000Sec
Photosensitivity	0,003 Lux @ F1,6 AGC on
System	Thermal image, True Day&Night
<b>Display</b>	
Image resolution max.	2592x1944
<b>DORI</b>	
Watch (62px/m)	27,3 m
Detect (125px/m)	14 m
Identify (250px/m)	7 m
Perceiving (25px/m)	68,5 m
<b>Functions</b>	
Analysis	Abandoned and Removed Objects (SOD), Attendance (FA), Crowds (CD), Enter Region, Face Capture (FD), Face Recognition (FR), Fire alarm, Heat Map (HM), Intrusion, Leave Region, Line crossing (LCD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD), Temperature Exception Alarm
Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Browser	Edge, Firefox, Google Chrome, MS Internet Explorer 10/11, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Eneo Privacy	Areas-ON/OFF switchable

# eneo INT-8SF0003M0A

## Continuation of the specifications

Internal memory	microSD card slot
Notes	
Remark	The viewing angles of the camera modules vary. We recommend only using components from the same brand together. You can find more information about our paid compatibility check with other brands at VIDEOR #229235.
Interfaces / Inputs/ Outputs	
Alarm inputs	1
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	Quick installation guide,drilling template,3x wall plugs with screws,1x Allen wrench,waterproof cover for RJ45 connector
Lens	
Horizontal angle of view	Optisch 81°,Thermal 56°
Vertical angle of view	Optisch 57°,Thermal 42°
Focal length	3,2 mm,3,6 mm
Lens Type	Prime lens
Video	
Image transfer rate max.	25 fps
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.265, M-JPEG
Product labeling:	
EAN/GTIN	4260229840603
Manufacturer order number	236317
Series	eneo IN-Serie

## Optional Accessory

SKU	Name	Description
233754	eneo AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
235257	eneo PM-21	Pole mounting adapter, steel for camera connection box AK-20, AK-21 and wall mount WB-24

# eneo INT-8SF0003M0A

Continuation of accessory

245272	eneo PM-21	Pole mounting adapter V2A stainless steel, for camera connection box AK-20, AK-21 and wall mount WB-24
218218	eneo Site Manager	Management Software for eneo IP products



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

