

eneo IAD-5SG1004MUC

SKU: 237369



Gigabit Switch, Unmanaged, 60W, 4x PoE, 1x RJ45, 1x SFP, 10/100/1000 Mbps, Desktop

Camera not included

Main Features

Gigabit PoE switch, desktop application

4x 10/100/1000 PoE+ ports, IEEE 802.3af/at

Gigabit uplink ports: 1x RJ45, 1x SFP

Up to 30W per port, total ≤60W.

Overvoltage protection IEC61000-4-5 (6KV).

Temperature range (operation) -5°C~45°C

CCTV mode enables transmission up to 250m @10Mbps

CCTV mode supports PoE watchdog function

Plug and Play, no settings required

Metal housing

Specifications

General	
Number of PoE ports	4
Design	Desktop
Dimensions (WxHxD) (extended)	27x135x86mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6
Weight	300 kg
Type	Unmanaged
Power consumption	65 W
Mounting type	Desktop
PoE Budget (Total)	60 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at

eneo IAD-5SG1004MUC

Continuation of the specifications

Power supply	48-57 VDC
Temperature Range (Operating)	-5°C ~ +45°C
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T, 1x 1000Base-X SFP, 4x 10/100/1000Base-T (PoE)
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket,PSU
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Security	CCTV mode
Internal Switching Capacity (Gbit)	12 Gbps
Internal Switching Capacity (MP per second)	8.9 Mpps
Product labeling:	
Manufacturer order number	237369

Optional Accessory

SKU	Name	Description
218758	eneo SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	eneo SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

