

IAD-5SG1004MUC

SKU: 237369



Abb. ähnlich

Gigabit Switch, Unmanaged, 60W, 4x PoE, 1x RJ45, 1x SFP, 10/100/1000 Mbps, Desktop

Main Features

Gigabit PoE switch, desktop application	Temperature range (operation) -5°C~45°C
4x 10/100/1000 PoE+ ports, IEEE 802.3af/at	CCTV mode enables transmission up to 250m @10Mbps
Gigabit uplink ports: 1x RJ45, 1x SFP	CCTV mode supports PoE watchdog function
Up to 30W per port, total ≤60W.	Plug and Play, no settings required
Overvoltage protection IEC61000-4-5 (6KV).	Metal housing

Specifications

General:	
Dimensions (HxWxD)	27x135x86mm
Construction	Desktop
Application	indoor
Trunk	IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,Contact discharge 6KV,Air discharge 8KV
Type	Unmanaged
Mounting	desktop
Blower	no
PoE ports (number)	4
Management	no
Supply voltage	48~57 VDC

IAD-5SG1004MUC

Continuation of the specifications

Power consumption	65W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
PoE budget	60 W
Operating temperature	-5°C ~ +45°C
Weight	300g
Functions:	
Multicast compliant	no
Port mirror	no
QoS	no
Security	CCTV Mode
SNMP	no
Parts supplied:	
Parts supplied	manual,power cord,Mounting Bracket,PSU
Network:	
Internal switching capacity (Gbit/s)	12 Gbps
Internal switching capacity (Mpps)	8,9 Mpps
Ethernet standards	IEEE 802.3 10BaseT,IEEE 802.3u 100BaseTX,IEEE 802.ab 1000BaseT,IEEE 802.3x Flow Control,IEEE 802.3at Power Over Ethernet (PoE+),IEEE 802.3af Power Over Ethernet (PoE)
VLAN	no
Interfaces / Inputs/ Outputs:	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T, 1x 1000Base-X SFP, 4x 10/100/1000Base-T (PoE)
Other	
Manufacturer order number	237369

Optional Accessory

SKU	Name	Description
219525	RJT-1000SFP	RJ45- SFP Transceiver Modul, 1000Base-T, 0°~ +70°C
216479	SFP-0850M10	SFP Modul, 1.25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
218758	SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216478	SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
216566	SFP-1310S10	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector, 0°~+70°C
216477	SFP-1310S40	SFP Modul, 1.25Gbps, 20km, Singlemode, 1310nm, Duplex LC Connector -40°~+75°C

IAD-5SG1004MUC

Continuation of accessory



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone:
Fax:
E-Mail:
Web:

+49 6074 - 888 - 300
+49 6074 - 888 - 100
info@eneo-security.com
www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

