eneo IAM-5SE1004IUP

SKU: 237908



Gigabit Switch, Unmanaged 120W, 4x PoE, Industrial Design -20°C~+65°C, PD port

Main Features

- Gigabit PoE Switch, DIN Rail
- 4x 10/100/1000 PoE ports, IEEE 802.3af/at/bt
- Maximum 90W power budget
- 1 x SFP Gigabit uplink port
- 1 x RJ45 Gigabit uplink port, PD-capable (90W PoE input)
- CCTV mode, extended transmission distance
- 1 x output relay
- Overvoltage protection IEC61000-4-5 (6KV)
- Temperature range -20°C ~ +65°C

Specifications

General	
Number of PoE ports	4
Design	DIN Rail Module
Dimensions (WxHxD) (extended)	44x110x160mm
Application environment	inside
ESD protection	IEC61000-4-2
Weight	540 kg
Type	Unmanaged
Power consumption	130 W
Mounting type	DIN Rail
PoE Budget (Total)	120 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt

© Copyright eneo by VIDEOR E. Hartig GmbH, November 8, 2026 -Technical changes reserved

eneo IAM-5SE1004IUP

Continuation of the specifications

Power supply	48-56VDC, Poe
Temperature Range (Operating)	-40°C ~ +65°C
Notes	
Remark	Power supply unit is not included in the scope of delivery,To achieve the specified PoE budget (total) value,please use suitable power supplies or PoE injector.PoE budget: 90W max. for a single PoE port; 75W max. for all PoE ports when supplied via PD por
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1x 10/100/1000Base-T (PoE-PD), 1x 1000Base-X SFP, 4x 10/100/1000Base-T
Parts supplied	
Scope of delivery	manual,power cord,Mounting Bracket
Network	
Eneo _netzwerkstandards	IEEE 802.1D Spanning Tree Protocol, IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3x Flow Control
Internal Switching Capacity (Gbit)	12 Gbps
Internal Switching Capacity (MP per second)	8.9 Mpps
Product labeling:	
Manufacturer order number	237908
Series	eneo Switch

© Copyright eneo by VIDEOR E. Hartig GmbH, November 8, 2026 -Technical changes reserved