

eneo IND-58F0002MTDA

SKU: 238644



Network Dome Camera Fix, Turret, Panorama 180°, 2x 5120x1440, Day/Night, DWDR, AI, 2x 2,8mm, IR, White Light, 12VDC, PoE, IP67

Main Features

Multisensor 2x 1/2.7' CMOS sensor, panorama
Maximum resolution 5120x1440 pixels each, 15fps
Panorama ultra wide-angle camera 180° HFoV, 32:9
AI analysis functions including object classification
WDR, BLC, HLC and 3D-DNR noise reduction
Lenses with 2.8mm fixed focal length

Smart Codec H.265/H.264, dual streaming
Browser-independent (Edge, Safari, Firefox, Chrome)
Supports ONVIF profiles S/T/G/M and audio
Local storage via micro SD card
NDAA compliance
Integrated IR and white light LED illumination, IP67

Specifications

General	
Heating	No
Lighting	Infrared, White
Dimensions (WxHxD) (extended)	112,4x135mm
Illumination range	Approx. 30 m , Approx. 15 m Warm light
ESC	1/5 ~ 1/20.000sec.
Weight	0.765 kg
SDK	upon request
Text overlay	Switchable on/off
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request

eneo IND-58F0002MTDA

Continuation of the specifications

Housing type	Outside
Housing material	Aluminium
Camera Type	Panoramic camera
Power consumption	8.88 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Power supply	12VDC, Poe
Temperature Range (Operating)	-30°C ~ +60°C, @ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	D-WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	8 MP
Recording sensor	CMOS
Chip size	1/2,7"
Flickerless function	Yes
Camera shape	Minsters
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Day/night mode	Day,Night,Automatic,Time
White balance	Automatic,Manual
Photosensitivity	0,001 Lux bei F1,6
System	24h Color, True Day&Night
Day/night switching	Electronic
Display	
Image resolution max.	5120x1440
DORI	
Watch (62px/m)	23,8 m
Detect (125px/m)	11,7 m
Identify (250px/m)	5,5 m
Perceiving (25px/m)	60,1 m
Functions	
Analysis	Abandoned and Removed Objects (SOD), Crowds (CD), Enter Region, Heat Map (HM), Intrusion, Intrusion (PID), Leave Region, Line crossing (LCD), Manipulation (TD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)
Audio support	Yes
Motion detector	Yes

eneo IND-58F0002MTDA

Continuation of the specifications

Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,Red & blue flashing lights,Siren,Cloud Upload
Audio	2 Way Audio, Built-in microphone, Built-in speaker
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Japanese, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Internal memory	microSD card slot
Notes	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Interfaces / Inputs/ Outputs	
Alarm inputs	0
External connections	RJ-45,12VDC input (DC plug),connection cable approx.30cm,micro SD card slot 256 GB
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Network	
Network Protocols	DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IEE 802.1, IPv4, IPv6, NTP, PPPoE, RTP, RTSP, SMTP, TCP-IP, UDP, UPnP
Lens	
Horizontal angle of view	180°
Focal length	2,8 mm
Aperture Range (F)	F1,2
MOD (Minimum Object Distance)	2 m
Lens Type	Prime lens
Zoom Factor (Digital)	0
Video	
Image transfer rate max.	15 fps
Resolution (extended)	5120x1440,4608x1296,4096x1152,3840x1080,3072x864,1536x432,1024x288
Picture size	32:9
Data stream types	Dual Streaming
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	

eneo IND-58F0002MTDA

Continuation of the specifications

EAN/GTIN	4260229840726
Manufacturer order number	238644
Series	eneo IN-Serie

Optional Accessory

SKU	Name	Description
233754	eneo AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
236663	eneo DOME-WB8	Wall bracket for PTZ dome INP-54M2812M0A and IND-5 Dome Series
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
218218	eneo Site Manager	Management Software for eneo IP products



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

