

eneo INB-58F0308MLA

SKU: 241615



Network Camera Bullet, Ultra Low Light, 3840x2160, Day/Night, WDR, AI, 3-8mm, PoE, 12V, IP67

Main Features

1/1.8" Sony CMOS sensor, maximum resolution 8 MP/30fps	Smart Codec H.265 /H.264, multi-streaming
Very high light sensitivity	Browser-independent (Edge, Safari, Firefox, Chrome)
Colour images in the dark thanks to integrated white light	Supports ONVIF profiles S/T/G/M
AI analysis functions including object classification	Local storage via micro SD card
WDR and 3D DNR noise reduction	Supports audio, built-in speaker and microphone
Motorised varifocal lens F1.0/3.0-8.0mm	Integrated red/blue light deterrent, NDAA compliance

Specifications

General	
Heating	No
Sunshade canopy	Yes
Integrated wall mount	Yes
Audio compression	G.711
Lighting	White
Dimensions (WxHxD) (extended)	199.82 x 128.98 x 90.7mm
Illumination range	Approx 30m
ESC	1/5 ~ 1/20.000sec.
Weight	1.28 kg
SDK	upon request

eneo INB-58F0308MLA

Continuation of the specifications

Text overlay	Switchable on/off
Color (Housing)	RAL9003,Pantone P 179-1 / Other colors available upon request
Housing type	Outside
Housing material	Aluminium
Camera Type	Bullet Camera
Power consumption	6.5 W
Mounting type	Ceiling, Wall
ONVIF	ONVIF Profile G, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T
Power over Ethernet	IEEE 802.3af
Protection	IP67, NEMA 4X
Power supply	12VDC, Poe
Temperature Range (Operating)	-35°C ~ +60°C,@ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)
Wide Dynamic Range (WDR)	WDR
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Resolution standard	8 MP
Recording sensor	Chipset AX620A, CMOS, Sensor IMX678
Chip size	1/1,8"
Flickerless function	Yes
Camera shape	Bullet
Manual Electric Shutter (MES)	1-5~1-20,000sec.
Day/night mode	Yes
White balance	Automatic,Manual
Photosensitivity	0,0005 Lux bei F1.0
System	24h Color
Day/night switching	No
Display	
Image resolution max.	3840x2160
DORI	
Watch (62px/m)	28 - 60,2 m
Detect (125px/m)	13,3 - 29,9 m
Identify (250px/m)	6,1 - 14,8 m
Perceiving (25px/m)	71,6 - 150,2 m
Functions	
Analysis	Abandoned and Removed Objects (SOD), Attendance (FA), Crowds (CD), Enter Region, Face Attributes (AD), Face Capture (FD), Face Recognition (FR), Heat Map (HM), Intrusion, Intrusion (PID), Leave Region, License plate recognition (LPD), License plate recognition (LPR), Line crossing (LCD), Manipulation (TD), Object Classification Human / Vehicle (PD&VD), Passage count (CC), Queues (QD), Rare Sounds (RSD)

eneo INB-58F0308MLA

Continuation of the specifications

Audio support	Yes
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Multicast	Yes
Alarm processing	recording internal storage (SD card),E-Mail,HTTP,FTP,TCP,UDP,Red & blue flashing lights,Siren
Audio	Built-in microphone, Built-in speaker
Browser	Edge, Firefox, Google Chrome, Safari
Menu languages	English, French, German, Italian, Portuguese, Russian, Spanish, Turkish
Password	Administrator and User
Privacy Zone	Areas-ON/OFF switchable
Internal memory	SDHC Card, SDXC Card
Notes	
Remark	Face and license plate recognition require an SD card or an eneo IN recorder. For optimal results,use only eneo components. For mixed brands,we offer a compatibility check for a fee (info: item #229235 at VIDEOR).
Interfaces / Inputs/ Outputs	
Alarm inputs	1
External connections	RJ-45,12VDC input (DC socket),connection cable approx. 30cm,micro SD card slot 256 GB
Ethernet interface	100Base-T, 10Base-T
Control Interfaces	Ethernet
Parts supplied	
Scope of delivery	manual,bag of screws
Network	
Network Protocols	DDNS, DHCP, DNS, FTP, HTTP, HTTPS, IEE 802.1, NTP, RTP, RTSP, SMTP, TCP-IP, UPnP
Lens	
Horizontal angle of view	105 - 56°
Vertical angle of view	54 - 32°
Focal length	3 - 8 mm
Aperture Range (F)	F1,2
MOD (Minimum Object Distance)	3 m
Lens Type	Varifocal
Zoomfactor (optical)	2
Video	
Image transfer rate max.	30 fps
Resolution (extended)	3840x2160 (16:9),2592x1944 (4:3),3072x1728 (16:9),2592x1520 (16:9),2304x1296 (16:9),1920x1080 (16:9),640x480 (VGA),320x240 (QVGA)

eneo INB-58F0308MLA

Continuation of the specifications

Picture size	16:9, 4:3
Data stream types	Triple-Stream(Main/Sub/Mobile)
Video Compression	H.264, H.264+, H.265, H.265+, M-JPEG
Product labeling:	
EAN/GTIN	4260229840689
Manufacturer order number	241615
Series	eneo IN-Serie

Optional Accessory

SKU	Name	Description
233754	eneo AK-20	Camera connection box for Wall and ceiling mounting, IN Series Bullet Cameras
233775	eneo AK-21	Camera connection box for Wall and ceiling mounting, Bullet and Dome Cameras IN series
235339	eneo AK-24	Dual camera connection box for selected Bullet or Fix Dome IN-Series cameras
234989	eneo INsight	Control software for recorder IN- and MN-series
236198	eneo INsight Installation Tool	Supports adjustments for cameras with AI features for IN-series
234990	eneo INsight mobile	Mobile App for recorder IN- and MN-series
235257	eneo PM-21	Pole mounting adapter, steel for camera connection box AK-20, AK-21 and wall mount WB-24
218218	eneo Site Manager	Management Software for eneo IP products



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

