

# eneo MPC-52A0010M0B

SKU: 241967



1/3" HD Camera, 1920x1080, 10x AF Zoom  
5,1-51mm, T-WDR, HD-SDI, EX-SDI, TVI, Composite

## Main Features

1/2,8" 2,0 Megapixel Sony CMOS-Sensor  
Resolution max. 1920x1080, 1080p@60/50fps  
Optical 10x Auto Focus Zoom, 5,1~51mm  
Multisignal Output HD-SDI, EX-SDI, TVI, Composite  
WDR 120dB, DNR, motion detector  
Digital noise reduction (2D+3D)

Image stabilization, privacy masking, defog  
Privacy Masking, Defog  
Slow Speed Shutter  
Compact Housing  
Power Supply 12VDC

## Specifications

General	
Lighting	No
Dimensions (WxHxD) (extended)	62,2x59,2x99,6mm
Weight	0.36 kg
Text overlay	available
Color (Housing)	silvermetallic,black
Housing type	Inside
Housing material	Aluminium
Power consumption	3 W
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C, @ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)

# eneo MPC-52A0010M0B

## Continuation of the specifications

Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Zoom cameras
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	AUTO
Photosensitivity	0,003 Lux
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	31,3 - 302,4 m
Detect (125px/m)	15,2 - 150,3 m
Identify (250px/m)	7,5 - 75,5 m
Perceiving (25px/m)	78 - 763 m
Functions	
Analysis	Motion Detection
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Menu languages	Chinese, English, Japanese
Interfaces / Inputs/ Outputs	
Number of alarm outputs	1
External connections	1x SDI Signal (BNC),1x HD/SD Analog Signal (BNC),12VDC power input,RS-485,external day&night switching,Alarm output
Interface Protocols	Pelco D, Pelco P
Control Interfaces	Coaxitron (HD Protocol), RS-485
Video Outputs	Composite (FBAS)
Parts supplied	
Scope of delivery	manual
Lens	
Horizontal angle of view	57 - 6,2°
Vertical angle of view	34 - 3,5°
Focal length	5,1 - 51 mm
Aperture Range (F)	F1.6~F1.8
Lens Type	Auto Focus Zoom

# eneo MPC-52A0010M0B

## Continuation of the specifications

Zoom Factor (Digital)	0
Zoomfactor (optical)	10
Video	
Resolution (extended)	1920x1080,1280x720
Signal Format	Composite (FBAS), EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP
Horizontal resolution	700 TVL
Product labeling:	
EAN/GTIN	4260229841822
Manufacturer order number	241967

## Optional Accessory

SKU	Name	Description
219504	eneo WD-30	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

