

eneo MPC-52A0010M0B

SKU: 241967



1/3" HD Camera, 1920x1080, 10x AF Zoom
5,1-51mm, T-WDR, HD-SDI, EX-SDI, TVI, Composite

Main Features

1/2,8" 2,0 Megapixel Sony CMOS-Sensor
Resolution max. 1920x1080, 1080p@60/50fps
Optical 10x Auto Focus Zoom, 5,1~51mm
Multisignal Output HD-SDI, EX-SDI, TVI, Composite
WDR 120dB, DNR, motion detector
Digital noise reduction (2D+3D)

Image stabilization, privacy masking, defog
Privacy Masking, Defog
Slow Speed Shutter
Compact Housing
Power Supply 12VDC

Specifications

General	
Lighting	No
Dimensions (WxHxD) (extended)	62,2x59,2x99,6mm
Weight	0.36 kg
Text overlay	available
Color (Housing)	silvermetallic,black
Housing type	Inside
Housing material	Aluminium
Power consumption	3 W
Power supply	12VDC
Temperature Range (Operating)	-10°C ~ +50°C, @ Luftfeuchtigkeit 90% oder weniger (nicht kondensierend)

eneo MPC-52A0010M0B

Continuation of the specifications

Wide Dynamic Range (WDR)	WDR 120dB
Camera	
Backlight compensation	Yes
Low Speed Shutter	Yes
Recording sensor	CMOS
Chip size	1/2,8"
Flickerless function	Yes
Camera shape	Zoom cameras
Signal-to-noise ratio	50 dB
Day/night mode	Automatic,Day,Night,extern (Sensor)
White balance	AUTO
Photosensitivity	0,003 Lux
System	True Day&Night
Day/night switching	Switchable IR Filter (ICR)
Display	
Image resolution max.	1920x1080
DORI	
Watch (62px/m)	31,3 - 302,4 m
Detect (125px/m)	15,2 - 150,3 m
Identify (250px/m)	7,5 - 75,5 m
Perceiving (25px/m)	78 - 763 m
Functions	
Motion detector	Yes
Digital Noise Reduction (DNR)	Yes
Analysis	Motion Detection
Menu languages	Chinese, English, Japanese
Interfaces / Inputs/ Outputs	
Number of alarm outputs	1
External connections	1x SDI Signal (BNC),1x HD/SD Analog Signal (BNC),12VDC power input,RS-485,external day&night switching,Alarm output
Interface Protocols	Pelco D, Pelco P
Control Interfaces	Coaxitron (HD Protocol), RS-485
Video Outputs	Composite (FBAS)
Parts supplied	
Scope of delivery	manual
Lens	
Horizontal angle of view	57 - 6,2°
Vertical angle of view	34 - 3,5°
Focal length	5,1 - 51 mm
Aperture Range (F)	F1.6~F1.8
Lens Type	Auto Focus Zoom

eneo MPC-52A0010M0B

Continuation of the specifications

Zoom Factor (Digital)	0
Zoomfactor (optical)	10
Video	
Resolution (extended)	1920x1080,1280x720
Signal Format	Composite (FBAS), EX-SDI @ 2MP, HD-SDI @ 2MP, HD-TVI @ 2MP
Horizontal resolution	700 TVL
Product labeling:	
Manufacturer order number	241967

Optional Accessory

SKU	Name	Description
219504	eneo WD-30	Wall Mount Bracket with Ball Joint, 1/4" Camera Fixing Screw, Pantone Cool Grey 1C



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

