eneo NSUR-1008M0A

SKU: 242363



Gigabit Switch Rack, Unmanaged, 8x PoE, 2xSFP, max. 30W each Port, integrated Power Supply max. 150W

Main Features

8 RJ45 ports with 10/100/1000 Mbps	MAC address auto-learning & aging
2 Gigabit SFP fiber ports for uplink	Switching capacity: 20 Gbps backplane
8 PoE+ ports, up to 30W per port	Forwarding rate up to 14.88 Mpps
Total PoE power budget: 130 Watts	Jumbo frame support up to 10K bytes
Supports IEEE 802.3af/at standard	Sturdy metal case, 271×181×44mm
Store-and-forward switching mode	Operating temperature: 0-45°C

Specifications

General	
Fan	No
Management	No
Number of PoE ports	8
Design	Desktop
Dimensions (WxHxD) (extended)	44.5x271x181.5mm
Application environment	inside
ESD protection	IEC61000-4-2, IEC61000-4-5
Weight	0.6 kg
Type	Unmanaged
Power consumption	150 W

© Copyright eneo by VIDEOR E. Hartig GmbH, November 2, 2026 -Technical changes reserved

eneo NSUR-1008M0A

Continuation of the specifications

Mounting type	19" Rack Installation, Desktop
PoE Budget (Total)	130 W
Power over Ethernet	IEEE 802.3af, IEEE 802.3at
Power supply	100-240VAC
Temperature Range (Operating)	0°C ~ +45°C,@ Luftfeuchtigkeit 10%-90% (nicht kondensierend)
Interfaces / Inputs/ Outputs	
Ethernet interface	1000Base-T, 100Base-TX, 10Base-T
Ports	1000base-T
Parts supplied	
Scope of delivery	manual,19\" rack mount angle,power cord
Network	
Eneo _netzwerkstandards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX
Internal Switching Capacity (Gbit)	20 Gbps
Internal Switching Capacity (MP per second)	14.88 Mpps
Product labeling:	
EAN/GTIN	4260229841556
Manufacturer order number	242363
Series	eneo Switch

Optional Accessory

SKU	Name	Description
244698	eneo NSFP-00100RJ45	SFP module, transceiver, RJ45 connection, Cat.6A, supports 10G/5G/2.5 G/1G Ethernet up to 50m range, CAT6a, hot-pluggable
245203	eneo NSFP-00300DLC-Multimode	SFP module, transceiver, Multi Mode, 1250Mbps, up to 550m distance, Duplex LC optical connector
242377	eneo NSFP-20000DLC	SFP Module, 1.25 Gbps, 20KM, Duplex LC, Tx/Rx at 1310 nm, hot-plug, SFP MSA-compliant, Digital Monitoring
242376	eneo NSFP-20000SLC	SFP Modul Pair, 1.25 Gbps, 20 km, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242375	eneo NSFP-20000SSC	SFP Modul Pair, 1,25Gbps, 20KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242374	eneo NSFP-3000SLC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex LC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
242373	eneo NSFP-3000SSC	SFP Modul Pair, 1,25Gbps, 3KM, Simplex SC, Tx/Rx at 1310/1550nm, SFP MSA-compliant, Digital Monitoring
218759	eneo SFP-0850M10-10G	SFP Modul, 10Gbps, 300m, Multimode, 850nm, Duplex LC Connector, -5°~+70°C

© Copyright eneo by VIDEOR E. Hartig GmbH, November 2, 2026 -Technical changes reserved

eneo NSUR-1008M0A

Continuation of accessory

218758	eneo SFP-0850M40	SFP Modul, 1,25Gbps, 550m, Multimode, 850nm, Duplex LC Connector, -40° ~ +70°C
216567	eneo SFP-0850MM10	SFP Modul, 155Mbps , 2km, Multimode, 850nm, Duplex LC Connector, 0°~+70°C
216478	eneo SFP-1310M40	SFP Modul, 1.25Gbps, 550m, Multimode, 1310nm, Duplex LC Connector, -40°~+75°C
218760	eneo SFP-1310S10-10G	SFP Modul, 10Gbps, 10km, Singlemode, 1310nm, Duplex LC Connector, -5°~+70°C

© Copyright eneo by VIDEOR E. Hartig GmbH, November 2, 2026 -Technical changes reserved