EDC-IPC-2/24V

SKU: 74135



Pendant Mount Indoor Dome Housing with Clear Bubble 6.5", 24VAC

Main Features

Indoor housing for Fastrax I - III dome cameras	Supply voltage: 24VAC/50-60Hz
Clear bubble 6.5" (165mm)	Protection rating: IP66
Prepared for wall and ceiling mounting	Option: Wall and ceiling mount brackets, power box
Heater & blower kit included	Option: Connection cable #74143 & #74144

Specifications

Other	
Camera fixing	dome
Bubble	165mm (6.5"), clear acrylic plastic
Housing	Indoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	clear
Hosuing material	Aluminium
Heater	yes
Mounting	Wall or ceiling pendant mount
Power consumption	approx. 75W for heater, blower and incl. dome camera
Operating temperature	-45°C ~ +50°C
Protection rating	IP66
Weight	2.8kg

EDC-IPC-2/24V

Continuation of the specifications

	7	
Manufacturer order number	74135	

Optional Accessory

SKU	Name	Description
220314	EDC-WMB1-W	Wall Mount for PTZ Dome Cameras, white, with Mounting Kit

Stay informed and subscribe to the eneo newsletter