

EDC-IPC-2/24V

SKU: 74135



Pendant Mount Indoor Dome Housing with Clear Bubble 6.5", 24VAC

Main Features

Indoor housing for Fastrax I - III dome cameras	Supply voltage: 24VAC/50-60Hz
Clear bubble 6.5" (165mm)	Protection rating: IP66
Prepared for wall and ceiling mounting	Option: Wall and ceiling mount brackets, power box
Heater & blower kit included	Option: Connection cable #74143 & #74144

Specifications

Other	
Camera fixing	dome
Bubble	165mm (6.5"), clear acrylic plastic
Housing	Indoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	clear
Housing material	Aluminium
Heater	yes
Mounting	Wall or ceiling pendant mount
Power consumption	approx. 75W for heater, blower and incl. dome camera
Operating temperature	-45°C ~ +50°C
Protection rating	IP66
Weight	2.8kg

EDC-IPC-2/24V

Continuation of the specifications

Manufacturer order number	74135
---------------------------	-------

Optional Accessory

SKU	Name	Description
74125	EDC-AKS1	Power&Connection Box with Mounting Bracket for In/Outdoor, 230V-24VAC/3.0A
220314	EDC-WMB1-W	Wall Mount for PTZ Dome Cameras, white, with Mounting Kit



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

