EDC-OPS-2/24V

SKU: 74136





Pendant Mount Outdoor Dome Housing with Sunshield, Tinted Bubble 6.5", 24VAC

Main Features

Outdoor housing for Fastrax I - III dome cameras	Supply voltage: 24VAC/50-60Hz	
Tinted bubble 6.5" (165mm)	Protection rating: IP66	
Prepared for wall and ceiling mounting	Option: Wall and ceiling mount brackets, power box	
Sunshield, heater and blower kit included	Option: Connection cable #74143 & #74144	

Specifications

Other	
Camera fixing	dome
Bubble	165mm (6.5"), tinted acrylic plastic
Housing	Outdoor
Color (housing)	Pantone Cool Gray 1C
Color (bubble)	tinted
Hosuing material	Aluminium
Heater	yes
Mounting	Wall or ceiling pendant mount
Power consumption	approx. 75W for heater, blower and incl. dome camera
Operating temperature	-45°C ~ +50°C
Protection rating	IP66
Weight	3,6kg

EDC-OPS-2/24V

Continuation of the specifications

Manufacturer order number	74136	
Mandacturer order number	74100	

Optional Accessory

SKU	Name	Description	
74125	FDC-AKS1	Power&Connection Box with Mounting Bracket for In/Outdoor, 230V-24VAC/3.0A	

63322 Rödermark, Deutschland